

H.B.FULLER CO,315 S.HICKS RD.PALATINE,IL 60067 -- SC-840 -- 8040-00-262-9011

===== Product Identification =====

Product ID:SC-840

MSDS Date:01/01/1985

FSC:8040

NIIN:00-262-9011

MSDS Number: BDQDV

=== Responsible Party ===

Company Name:H.B.FULLER CO,315 S.HICKS RD.PALATINE,IL 60067

Emergency Phone Num:612-645-3401

CAGE:KO955

=== Contractor Identification ===

Company Name:H.B.FULLER CO,315 S.HICKS RD.PALATINE,IL 60067

CAGE:KO955

Company Name:HB FULLER CO.

Addres

s:315 SOUTH HICKS ROAD

Box:City:PALATINE

State:IL

ZIP:60067

Country:US

Phone:847-358-9500/612-236-5842

CAGE:5P957

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 17.0%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 15.0%

OSHA PEL:200 PP

M/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CYCLOHEXANONE (SARA III)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 5.0%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:HEADACHE,NAUSEA, DIZZINESS, IMPAIRMENT OF
COORDINATION

===== First Aid Measures =====

First Aid:INHALATION-
REMOVE TO FRESH AIR, ADMINISTER ARTIFICIAL
RESPIRATION IF NECESSARY. CALL DOCTOR. SKIN CONTACT-REMOVE WITH
MINERAL SPIRIT FOLLOWED BY SOAP & WATER. EYE CONTACT-FLOOD WITH
LARGE QUANTITIES OF WATER FOR 10 MIN.DO NOT INDUCE VOMIT.CALL
DOCTOR.

===== Fire Fighting Measures =====

Flash Point:0F TCC
Lower Limits:1.1
Extinguishing Media:CO2,FOAM,DRY CHEMICAL
Fire Fighting Procedures:DO NOT USE WATER
Unusual Fire/Explosion Hazard:VAPORS MAY IGNITE EXPL
OSIVELY, VAPORS MAY
CAUSE FLASH FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE OR EXTINGUISH ALL SOURCES OF
FLAME,HEAT,SPARKS.DISPOSE OF RAGS IN SEALED CONTAINERS. TURN OFF
ALL ELECTRIC MOTORS IN AREA AND VENTILATE THE AREA.WEAR RUBBER
GLOVES AND USE RAGS.

===== Handling and Storage =====

Handling and Storage Precautions:DANGER: EXTREMELY FLAMMABLE. VAPORS
MAY CAUSE FLASH FIRE.

O

ther Precautions:VAPORS HARMFUL. HARMFUL OR FATAL IF SWALLOWED

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED IF VENTILATION IS ADEQUATE
Ventilation:LOCAL EXHAUST-GENERAL DILUTION MECHAN.KEEP TLV BELOW 50 PPM
Protective Gloves:SOLV.RESISTANT
Eye Protection:SAFETY GLASSES/SIDE SHIEL
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:133-313F
Vapor Density:>1
Spec Grav
ity:0.90
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NO DENOTE
Appearance and Odor:LOW VISCOSITY SYRUP WITH SOLVENT (KETONE) ODOR
Percent Volatiles by Volume:76.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:FLAME,SPARK,HEAT
Hazardous Decomposition Products:CO,CO2,AND HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:LAND FILL UNLESS PROHIBITED BY LAW. OTHERWISE
INCINERATE.DO NOT INCINERATE SEALED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent pr
ofessional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.