

===== Product Identification =====

Product ID:921-02100 CATALYST, PART B

MSDS Date:01/01/1985

FSC:8010

NIIN:00-264-8866

MSDS Number: BDQXC

=== Responsible Party ===

Company Name:SCM-GLIDDEN COATINGS & RESINS DIV

Address:925 EUCLID AVE

City:CLEVELAND

State:OH

ZIP:44115

Country:US

CAGE:DO630

=== Contractor Identification ===

Company Name:GLIDDEN CO MEMBER OF ICI WORLD PAINTS

Addr

ess:925 EUCLID AVE

Box:15049

City:CLEVELAND

State:OH

ZIP:44115

Country:US

Phone:216-344-8000

CAGE:72818

Company Name:SCM-GLIDDEN COATINGS & RESINS DIVISION

Address:925 EUCLID AVENUE

City:CLEVELAND

State:OH

ZIP:44115

Phone:(216) 826-5566

CAGE:DO630

===== Composition/Information on Ingredients =====

Ingred Name:2-ETHOXYETHANOL (EGEE) (SARA III)

CAS:110-80-5

RTECS #:KK8050000

Fraction by Wt: 24%

OSHA PEL:S,200 PPM

ACGIH TLV:S, 5 PPM; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 L

BS

Ingred Name:DIETHYLENE TRIAMINE
CAS:111-40-0
RTECS #:IE1225000
Fraction by Wt: 8%
OSHA PEL:1 PPM
ACGIH TLV:S, 1 PPM; 9192

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 24%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 24%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000
LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:EYE,SKIN, RESP TRACT IRRIT. HEADACHE, DIZZ,
UNCONSCIOUSNSS, OR COMA. DERMATITIS ON PROLNGD CONTACT

===== First Aid Measures =====

First Aid:FUMES:MOVE TO WELL VENTILATED AREA;RESTORE BREATHING; CALL
MD. SKIN:WIPE W/CLEAN CLOTH; WASH THORLY W/SOAP & WATER. EYE:FLUSH
THOROUGHLY W/WATER. CALL MD.

===== Fire Figh

ting Measures =====

Flash Point:60 F TCC

Lower Limits:1.0

Extinguishing Media:CO*2, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:H*2O MAY BE INEFFECT,BUT USE TO COOL HEAT
EXPOSED CONTAINERS

Unusual Fire/Explosion Hazard:KEEP AWAY FROM SOURCES OF IGNITION.

CONTNRS MAY EXPLODE W/EXTREME HEAT: DO NOT APPLY TO HOT SURFACE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION; VENTILATE
AREA; MOP S

PILLS W/INERT ABSORBENT. BURN SWEEPINGS IN SAFE AREA-MFG
REC.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 100 F. KEEP CONTAINERS
CLOSED & AWAY FROM SOURCES OF IGNITION.

Other Precautions:AVOID PROLONGED CONTACT W/SKIN & BREATHING VAPORS OR
SPRAY MIST. DO NOT TAKE INTERNALLY. VAPOR PRESSURE GIVEN IS FOR
METHYL ISOBUTYL KETONE.

===== Exposure Controls/Personal Protection =====

Respiratory Pro

tection:NIOSH/MSHA APPRVD DEVICE FOR EXPOSURE OF CONCERN

Ventilation:DILUTION OR LOCAL EXHAUST TO KEEP VAPORS BELOW TLV

Protective Gloves:SOLVENT RESIST

Eye Protection:SPLASH PROOF GOGGLES

Supplemental Safety and Health

PART B OF 2-PART PRODUCT. PART A IS 921R 2104. CONFORMS TO MIL SPEC
MIL-P-52192 B.KEY1:J1.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:237 TO 419F

Vapor Pres:15

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:83.9

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID CONTAM W/FOREIGN MATERIALS

Hazardous Decomposition Products:CO & POSSIBLE NITROUS FUMES ON
IGNITION NO

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE IN
ACCORD W/LOCAL,STATE, & FEDERAL REGULATIONS.

Disclaimer (provid

ed with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.