View NSN Online: https://aerobasegroup.es/nsn/9150-00-273-2397

Product ID:BRAYCO 363 MSDS Date:11/13/1990 FSC:9150 NIIN:00-273-2397 MSDS Number: BDSBD === Responsible Party === Company Name: CASTROL INC., SPECIALTY PRODUCTS DIVISION Address:16715 VON KARMAN AVE., SUITE 230 City:IRVINE State:CA ZIP:92714 Country:US Info Phone Num:714-660-9414 Emergency Phone Num:800-424-9300, CHEMTREC Preparer's Name:KAREL WRIGHT CAGE:EO309 === Contractor Identification === Company Name: CASTROL INC., SPECIALTY PRODUCTS DIV Address:1001 W 31 STREET **City:DOWNERS GROVE** State:IL ZIP:60515 Country:US Phone:708-241-4000 CAGE:EO309 Company Name: CASTROL INDUSTRIAL NORTH AMERICA INC SPECIALTY PRODUCTS DIV Address:1001 WEST 31ST STREET Box:City:DOWNERS GROVE State:IL ZIP:60515-1280 Country:US Phone:800-621-2661/ FAX: 630-241-4140 CAGE:2R128

====== Composit

ion/Information on Ingredients ==========

Ingred Name:NO HAZARD INGREDIENTS STATED BY MANUFACTURERS Fraction by Wt: 100% Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: BELIEVED TO BE MODERATELY IRRITATING TO EYES, SLIGHTLY IRRITATING TO SKIN. PROLONGED OR REPEATED SKIN CONTACT MAY RESULT IN VARIOUS SKIN DISORDERS SUCH AS DERMATITIS. INHALATION OF VAPORS GENERATED AT HIGH TEMPERATURES OR MISTS MAY IRRITATE RESPIRATORY TRACT. Explanation of Carcinogenicity: THIS PRODUCT IS NOT CONSIDERED HAZARDOUS BY THE MANUFACTURER. Effects of Overexposure: SKIN IRRITATION, DEFATTING, DERMATITIS. **RESPIRATORY IRRITATION.** Medical Cond Aggravated by Exposure:NONE KNOWN First Aid:INHALATION:REMOVE TO FRESH AIR. RES USCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING, WASH WITH SOAP AND WATER, IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION. Flash Point Method:COC Flash Point:280F ,138C Extinguishing Media: USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard: DO NOT USE WATER EXCEPT AS FOG OR SPRAY TO COOL CONTAINERS OR TANKS TO AVOID HEATING ABOVE FLASH PT

Spill Release Procedures: DO NOT PERMIT

PRODUCT TO ENTER STREAMS, SEWERS OR OTHER WATERWAYS. DIKE SPILL AND ELIMINATE LEAK. ABSORB WITH INERT MATERIAL AND STORE IN CLOSED CONTAINERS UNTIL DISPOSAL. Neutralizing Agent:NOT APPLICABLE.

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATH E MIST. AVOID

PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

Respiratory Protection: IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED ORGANIC VAPOR CARTRIDGE AND DUST/MIST PRE-FILTER RESPIRATORS AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/ WARNINGS AND NIOSH-RESPIRATOR SELECTIO

N.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE. LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED. Protective Gloves:NEOPRENE, NITRILE, VPC OR NATURAL RUBBER Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING O

R

FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS.

HCC:V6 Boiling Pt:B.P. Text:>400F,>204C Spec Gravity:0.88 Solubility in Water:NEGLIGIBLE Appearance and Odor:BROWN FLUID, SLIGHT PETROLEUM ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AG

ENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, SMOKE, FUMES, AND OXIDES OF SULFUR.

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. MAY BE DISPOSED OF BY CONTROLLED INCINERATION.

Disclaimer (provided with this information by th e compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.