

CSD, INC -- DRY CLEANING SOLVENT -- 6850-00-281-1985

=====
Product Identification
=====

Product ID: DRY CLEANING SOLVENT

MSDS Date: 01/01/1987

FSC: 6850

NIIN: 00-281-1985

MSDS Number: BDSPM

=== Responsible Party ===

Company Name: CSD, INC

Address: 5 HACKBURY ST

Box: 687

City: CONROE

State: TX

ZIP: 77305

Country: US

Info Phone Num: 409-756-1065

Emergency Phone Num: 409-756-1065

CAGE: 0LWP6

=== Contractor Identif

ication ===

Company Name: CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address: 2210 HACKBERRY LN

Box: 687

City: CONROE

State: TX

ZIP: 77305

Country: US

Phone: 409-756-1065

CAGE: 4N760

Company Name: CSD, INC

Box: 687

City: CONROE

State: TX

ZIP: 77305

Country: US

Phone: 800-424-9300

CAGE: 0LWP6

=====
Composition/Information on Ingredients
=====

Ingred Name: MINERAL SPIRITS

CAS: 64475-85-0

RTECS #: PY8240000

Fraction by Wt: 100%

ACGIH TLV: 350 PPM

=====
Hazards Identification
=====

=====
Effects of Overexposure: INHAL OF HIGH VAPOR CONCENTRAT MAY HAV RESULTS RANGNG FR DIZZI & HEADNESS TO UNCONSCIOUSNESS.

=====
First Aid Measures

First Aid: IF OVERCOME BY VAPOR, REMOV FROM EXPOSURE IMMEDIATELY; CALL A DR. IF BREATHING IS IRREG OR STOPPED, START RESUSCITATION, ADMIN. OXYGEN. IF INGESTED, DO NOT INDUCE VOMITING, CALL A DR. IN CASE OF SKIN CONTACT, REMOV ANY CONTAMINATED CLOTHING.

=====
Fire Fighting Measures

Flash Point: 108F TCC 42C T

Lower Limits: 0.9%

Upper Limits: 6.0%

Extinguishing Media: FOAM, DRY CHEM, CO₂ OR WATER FOG OR SPRAY

Fire Fighting Procedures: AIR-SUPPLIED BREATHING EQPMT F/ENC AREAS. COOL EXPOS CONTNR

Unusual Fire/Explosion Hazard: DO NOT MIX OR STORE W/STRONG OXIDANTS LIKE LIQUID CHLORIDE OR CONCENTRAT OXYGEN. COMBUSTIBLE LIQUID.

=====
Accidental Release Measures

Spill Release Procedures: REMOV ALL IGNIT SOURCES. KP PEOPLE AWAY. RECOVER

FREE LIQUID ADD ABSORBENT (SAND, EARTH, SAWDUST, ETC.) TO SPILL AREA. AVOID BREATHING VAPORS. VENTILAT CONFINED SPACES. OPN ALL WINDOWS/DOORS. KP PETROL PRODUCTS OUT OF SEWERS/WATRCOURSES BY DIKING OR IMPOUNDING

=====
Handling and Storage

Handling and Storage Precautions: KP CONTNRS CLOS WHN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS. ADEQ*VENT REQD. *ADEQ MEANS EQUIVAL TO OUTDOORS.

Other Precau

tions: AVOID BREATHING VAPORS. AVOID PROLNG/REPEAT CONTACT WITH SKIN. REMOV CONTAM CLOTHING, LAUNDR BEFORE REUSE. REUSE CONTAM SHOES & THORO DRY BEFORE REUSE. WASH SKN THORO W SOAP/WATR AFTR CONTACT.

=====
Exposure Controls/Personal Protection

Respiratory Protection: USE HYDROCARBN VAP CANISTR OR SUPPLIED-AIR RESPIRATORY PROTCT IN CON

Ventilation: LOC EXHAUS-FACE VELOCITY >60 FPM USE ONLY W/ADEQ VENTIL.

Protective Gloves: CHEM-RESISTANT

Eye Protection: SPLASH GOGG OR FACE SH

IEL

Other Protective Equipment:CHEM-RESISTANT APRON RECOMMENDED

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300F,149C

Vapor Density:4.8

Evaporation Rate & Reference:N-BUTYL ACET