

GLYPTAL INC -- GLYPTAL ALKYD 1201 RED EMAMEL -- 5970-00-284-5448

===== Product Identification =====

Product ID:GLYPTAL ALKYD 1201 RED EMAMEL

MSDS Date:01/26/1989

FSC:5970

NIIN:00-284-5448

MSDS Number: BDTKD

=== Responsible Party ===

Company Name:GLYPTAL INC

Address:305-EASTERN AVENUE

City:CHELSEA

State:MA

ZIP:02150-3344

Country:US

Info Phone Num:617-884-6918

Emergency Phone Num:617-884-6918

Prepar

er's Name:TECHNICAL STAFF

CAGE:65313

=== Contractor Identification ===

Company Name:GLYPTAL INC

Address:305 EASTERN AVE

Box:NONE

City:CHELSEA

State:MA

ZIP:02150-3344

Country:US

Phone:617-884-6918

CAGE:65313

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 24.0%

Other REC Limits:150 PPM (STEL)

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt

Qty:1000 LBS

Ingred Name:V M & P NAPHTHA
CAS:64742-89-8
Fraction by Wt: 4.5%
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: 31.3%
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:PIGMENT
Other REC Limits:2MG/CUM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE EYE AND LIVER DAMAGE AND
CENTRAL NERVOUS SYSTEM DEPRESSION.
Medical Condition Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER FOR AT LEAST 15 MINUTES.SEE DOCTOR.
SKIN:REMOVE CONTAMINATED CLOTHING AND SHOES.WASH WITH SOAP AND
WATER.USE HAND LOTION. INHALATION:REMOVE TO FRESH AIR.GIVE
OXYGEN/CPR IF NEEDED IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:72.0F,22.2C
Lower Limits:1.0
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER
FOG.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:EXPLOSION HAZARD IN CONTAINERS FROM
PRESSURE BUILDUP DUE TO HEAT.

===== Accidental

Release Measures =====

Spill Release Procedures:REMOVE HEAT AND IGNITION SOURCES.PROVIDE ADEQUATE VENTILATION. COLLECT SPILL W/ABSORBENT, PLACE IN CLOSABLE CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,WELL VENTILATED AREA.AVOID EXCESS HEAT & IGNITION SOURCES.GROUND CONTAINERS & TRANSFER VESSELS. KEEP LIQ FREE-FALL SHORT TO AVOID STATIC
Other Precautions:DO NOT INGEST. AVOID PROLONGE
D BREATHING OF VAPORS
AND SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE TLV/PEL.
Ventilation:LOCAL EXHAUST TO KEEP VAPORS BELOW TLV. USE EXPLOSION-PROOF MOTORS AND EQUIPMENT.
Protective Gloves:NEOPRENE.
Eye Protection:CHEMICAL GOGGLES.
Other Protective Equipment:AS REQD TO AVOID SKN CONTACT.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.LAUNDER
CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:242-287F
Vapor Density:>1.0
Spec Gravity:1.20
Evaporation Rate & Reference: