

CON-LUX COATINGS INC -- ENAMEL, ALKYD, GLOSS 14110 -- 8010-00-286-7727

=====
Product Identification
=====

Product ID:ENAMEL, ALKYD, GLOSS 14110

MSDS Date:01/01/1985

FSC:8010

NIIN:00-286-7727

MSDS Number: BDTWR

=== Responsible Party ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:908-287-4000 / FAX 908-287-9288

Emer

gency Phone Num:908-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 46.0%

OSHA PEL:100 PPM

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 M

G/M3)
CAS:7758-97-6
RTECS #:GB2975000
Fraction by Wt: 8.3%
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.05MG/M3(CR)A2;8990

===== Hazards Identification =====

Effects of Overexposure:IRRITATION OF EYES AND SKIN. IRRITATION OF
RESPIRATORY TRACT.HEADACHE,DIZZY.

===== First Aid Measures =====

First Aid:SKIN/EYES:FLUSH WITH PLENTY OF WATER. INHAL:MOVE TO FRESH
AIR. IF IRRITATION PERSISTS CALL A DR.

===== Fire
Fighting Measures =====

Flash Point:40.6/105 TCC
Lower Limits:0.9
Upper Limits:6.0
Extinguishing Media:CLASS B EXTINGUISHERS (CO*2,DRY CHEM. OR FOAM)
Fire Fighting Procedures:USE WATER TO COOL CLOSED CONTAINERS & PREVENT
AUTOIGNITION
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED AND
ISOLATE FROM SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT
SURFACES,ELECTRICAL,STATIC OR FRICTIONAL SPARKS) AVOID BREATHING OF
VAPORS.VENTILATE AREA.REMOVE WITH NON-SPARKING TOOLS AND INERT
ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMP. KEEP
AWAY FROM OPEN FLAMES AND SPARKS.
Other Precautions:DO NOT TAKE INTERNALLY. CONTANERS SHOULD BE GROUNDED
WHEN POURING.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

===== Exposure Controls/Pe

Personal Protection =====

Respiratory Protection: BUREAU OF MINES APPROVED CHEM/MECH FILTER
RESPIRATOR

Ventilation: LOCAL EXHAUST

Protective Gloves: YES

Eye Protection: SAFETY GLASSES OR GLASSES

Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT WITH
CONTAMINATED CLOTHING

Supplemental Safety and Health

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY
TO HOT SURFACES.

===== Physical/Chemical Properties =====

HCC: F4

Boiling

Point: B.P. Text: 157.2/315

Vapor Pressure: 1

Vapor Density: 4.7

Specific Gravity: 1.02

Evaporation Rate & Reference: BUAC=1: 0.15

Solubility in Water: 0

Appearance and Odor: GREEN LIQUID, MILD ALIPHATIC ODOR.

Percent Volatiles by Volume: 60

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: CO, CO₂

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND

FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume r

responsibility for the suitability of this information to their particular situation.