Product ID:14110 GREEN MSDS Date:01/01/1985 FSC:8010 NIIN:00-286-7727 **MSDS Number: BDTWS** === Responsible Party === Company Name: PRAXAIR INC Address:39 OLD RIDGEBURY RD City:DANBURY State:CT ZIP:06817-0001 Country:US Info Phone Num:203-794-5782 Emergency Phone Num:203-794-5782 CAGE:0LV01 === Contractor Identification === **Company Name: PRATT AND LAMBERT INC** Box:6027 City:CLEVELAND S tate:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196 Company Name: PRAXAIR, INC. Address:39 OLD RIDGEBURY RD Box:City:DANBURY State:CT ZIP:06810-5113 Country:US Phone:800-772-9247; 800-PRAXAIR CAGE:0LV01

Ingred Name:MINERAL SPIRITS CAS:64475-85-0 RTECS #:PY8240000 Fraction by Wt: 45% ACGIH TLV:500 PPM

Ingred Name:TRIETHYLAMINE (SARA III) CAS:121-44-8 RTECS #:YE0175000 Fraction by Wt: 0.5%

======= H

Effects of Overexposure: IRRIT OF NOSE, THROAT, EYES & POSS DIZZINESS & NAUSEA. SPRAY MIST CONTN LEAD.

First Aid:INHAL:REMOVE FR EXPOSR & PROVID FRESH AIR.SPLASH EYES-FLUSH IMMED W/LG AMTS OF WATER FOR 15 MIN.SPLASH SKIN:REMOV CONTAM CLOTHING & WASH ALL AFFECT AREA W/WATR.INGEST:DO NOT INDUC VOMITNG.CONSULT A DR . IMMED IN ALL CASES.

======= Fire Fighti

ng Measures =================

Flash Point:104 F 40 C TCC

- Extinguishing Media:CLASS B EXTING, CARBON DIOXIDE, DRY CHEM OR ALCOHOL FOAM
- Fire Fighting Procedures:SELF CONTAINED BREATH APPARAT WATER MAY BE INEFECTIVE.
- Unusual Fire/Explosion Hazard: KEEP CONTNRS TIGHTHLY CLOS. ISOLAT FR HEAT, ELECTR EQPMT, SPARKS & OPN FLAME. DO NOT APPLY TO VRYHOT SUR

Spill Release Procedures: REMOV ALL SOURCES OF IGNIT (FLAMES, HOT

SURFACES, ELECTRICAL, STATIC OR FRICRTIONAL SPARKS). VENTILAT ATEA & AVOID BREATHING VAPORS. REMOV W/ INERT ABSORB & NON-SPARKING TOOLS. STEPS MUST BE TAKN TO PREVNT CONTAM OF GROUND WATR OR STREAMS.

Handling and Storage Precautions:DO NOT STORE ABOV 120 F.STORE LG QUANTITIES IN COMPLIA W/OSHA 1910.106.CONTNRS SHLD BE GROUNDED & BONDED TO THE RECEIVING CONTNR.

Other Precautions:DO NOT CUT OR WELD ON EMPTY CONT AINER. DO NOT USE

UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER.

- Respiratory Protection:NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY WHN SPRAYING IN OUTDR
- Ventilation:PROVID GEN DILUT/LOC EXHAUST VENT TO KP CONCENT BELO ACEP TL
- Protective Gloves:SOLVENT, IMPERME
- Eye Protection:SAFETY EYEWR

Other Protective Equipment: PROTECTV EQPMT TO PRVNT SKN CONTCT.SE

OSHA,29 CFR 1910.1025

Sup

plemental Safety and Health

HCC:F4 Boiling Pt:B.P. Text:311-373F Vapor Density:>AIR Evaporation Rate & amp; Reference:>ETHER Percent Volatiles by Volume:60

Stability Indicator/Materials to Avoid:YES AVOID CONTCT W/STRONG ACIDS OR AKALINE MATERIALS. Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES. Hazardous Decomposition Products:BURNING WILL PRODUCE S MOKE & OXIDES OF CARBON & LEAD. Conditions to Avoid Polymerization:DO NOT ADD DRIERS OR REACTIV CHEM W/O TECHN SUPERVISION.

Waste Disposal Methods:DISPOSE IN ACCORD W/LOCAL, STATE & FEDERAL REGULATIONS.INCINERATIN EPA APPRVD FACILITY.DO NOT INCINERAT CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.