Product ID: ENAMEL ALKYD GLOSS GRAY 16187 MSDS Date:01/01/1987 FSC:8010 NIIN:00-286-7749 **MSDS Number: BDTXP** === Responsible Party === Company Name: PRATT AND LAMBERT Address:16116 E 13TH ST Box:2153 City:WICHITA State:KS ZIP:67201 Country:US CAGE:61196 === Contractor Identification === **Company Name: PRATT AND LAMBERT INC** Box:6027 City:CLEVELAND State:OH ZIP:4 4101-1027 Country:US Phone:216-566-2902 CAGE:61196

Ingred Name:MINERAL SPIRITS CAS:64475-85-0 RTECS #:PY8240000 ACGIH TLV:100PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:IRON OXIDE CAS:1309-37-1 RTECS #:NO7400000 OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293
======================================
Effects of Overexposure:PNEUMOCONIOSIS,PERMANENT NERVOUS SYSTEM DAMAGE,INTERNAL ORGAN DAMAGE.DELIBERATE INHALATION HARMFUL.
======================================
First Aid:INGESTION:GET IMMEDIATE MEDICAL ATTENTION.INHALATION:REMOVE TO FRESH AIR.RESTORE BREATHING.KEEP WARM AND Q UIET.CONSULT
PHYSICIAN.EYES:15 MINUTE WATER FLUSH.CONSULT PHYSICIAN.SKIN:REMOVE CONTAMINATED C LOTHING.WASH SKIN WITH SOAP & WATER.
======================================
Flash Point:80F,27C Extinguishing Media:CARBON DIOXIDE,DRY CHEMICALS,ALCOHOL,POLYMER FOAMS. Fire Fighting Procedures:SELF-CONTAINED BREATHING APPAR.WATER-FOG TO COOL CONTAINERS.
Unusual Fire/Explosion Hazard:CONTAINER EXPLOSION HAZARD DUE TO EXTREME HEAT,EXPOSURE TO SOURCES OF IGN ITION.
======================================
Spill Release Procedures:REMOVE SOURCES OF IGNITION.CONTAIN WITH INERT MATERIAL.TRANSFER TO COVERED METAL CONTAINERS.PREVENT ENTRY TO DRAINS,SEWERS AND GROUND WATER,WEAR RESPIRATORS,EYE,SKIN PROTECTION.REMOVE LIQUID WITH INER T ABSORBENT AND NON-SPARKING TOOLS.

Handling and Storage	Precautions:DO NO	T STORE ABC	OVE120F.STORE	LARGE
QUA				

NTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.CLOSE CONTAINER AFTER USE.DO NOT BREATHE FUMES,SANDING PARTICLES. Other Precautions:DO NOT WELD,CUT OR BRAZE EMPTY CONTAINER.DO NOT CLEAN AND RE-USE CONTAINER.DO NOT USE PRESSURE TO EMPTY CONTAINER.GROUND AND BOND CONTAINER TO RECEIVING VESSEL.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH APPROVED CHEMICAL/MECHANICAL FILTER RESPR;AIR SUPPLIED RESPR. Ventilation:LOCAL VENTILATION/EX HAUST TO REMOVE DECOMPOSITION BYPRODUCTS Protective Gloves:SOLVENT RESIST. Eye Protection:FACE SHIELD;SHIELDED SPEC Other Protective Equipment:PROTECTV EQPMT TO PRVNT SKN CONTCT.SE OSHA,29 CFR 1910.1025 Supplemental Safety and Health

HCC:F4 Boiling Pt:B.P. Text:193F,89C Vapor Density:>AIR Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:58

================== Stability and Reactivity Data

\_\_\_\_\_

Stability Indicator/Materials to Avoid:YES STRONG ACIDS,ALKALINES,OXIDIZERS. Stability Condition to Avoid:EXCESSIVE HEAT.SOURCES OF IGNITION. Hazardous Decomposition Products:CO,CO\*2,SMOKE FROM IGNITION Conditions to Avoid Polymerization:DO NOT ADD DRIERS OR REACTIV CHEM W/O TECHN SUPERVISION.

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS.DISPOSE OF IN ACCORDANCE WITH EPA,LOCAL,STATE A

## ND FEDERAL REGULATIONS FOR FLAMMABLE, HAZARDOUS WASTES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.