View NSN Online: https://aerobasegroup.es/nsn/8010-00-290-4054

Product ID:IVORY

MSDS Date:01/01/1987

FSC:8010

NIIN:00-290-4054

MSDS Number: BDVDP === Responsible Party ===

Company Name: CORONADO PAINT CO INC., 308 OLD COUNTY EDGEWATER FL

Emergency Phone Num:904-428-6461

CAGE:33200

=== Contractor Identification ===

Company Name: CORONADO PAINT COMPAN

Y, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812 Country:US

Phone:904-428-6461

CAGE:33200

======= Composition/Information on Ingredients ========

Ingred Name: ALKYD RESIN

Fraction by Wt: 30.0%

Ingred Name: PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS:8002-05-9

RTECS #:SE7449000 Fraction by Wt: 19.0% OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 8990

========== Hazards Identification =============

Effects of Overexposure:PRODUCES S

EVERE IRRITATION DRYING OF SKIN.EXCESSIVE INHALATION CAUSES HEADACHE, DIZZINESS, NAUSEA.
======================================
First Aid:EYE CONTACT FLUSH W/WATER,SKIN CONTACT:WASH W/MILD SOAP & WATER & APPLY SKIN CREAM. INHALATION:REMOVE TO FRESH AIR AND CALL MD. APPLY ARTIFICIAL RESPIRATION,IF NECESSARY.
======================================
Flash Point:102F SETA Lower Limits:0.8 Upper Limits:5.0 Extinguishing Media:FO AM CARBON DIOXIDE DRY CHEMICAL. Fire Fighting Procedures:TREAT AS CLASS B FIRE Unusual Fire/Explosion Hazard:VAPOR MAY EXPLODE WHEN MIX WITH AIR. ===================================
METAL SURFACES. ===================================
Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS
OPEN FLAME.USE WITH ADEQUATE VENTILATION.AVOID PROLONGED OR REPEATED SKIN CONTACT.
====== Exposure Controls/Personal Protection =======
Respiratory Protection:SELF CONTAINED NIOSH APPROVED RESPIRATOR IF NECESSARY. Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV. Protective Gloves:IMPERVIOUS Eye Protection:CHEMICAL GOGGLES Other Protective Equipment:EYE BATH & SAFETY SHOWER Supplemental Safety and Health ===================================

====

HCC:F4

Boiling Pt:B.P. Text:315F (157C)

Vapor Pres:80 Vapor Density:4.9 Spec Gravity:0.903

Evaporation Rate & Department Reference: SLOWER THAN NBUACT

Solubility in Water: NEGLIGIBLE

Appearance and Odor:PETROLEUM DISTILLATE ODOR IVORY OPAQUE LIQUID

Percent Volatiles by Volume:64.0

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS. Stability Condition to Avoid:EXCESSIVE HEAT,SPARK,OPEN FLAME. Hazardous Decomposition Prod ucts:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE.

======= Disposal Considerations ============

Waste Disposal Methods:LANDFILL,INCINERATION UNDER SAFE SUPERVISED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims

all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.