

ALLIED CHEMICAL CORPORATION -- GENETRON 12 -- 6830-00-292-0147

===== Product Identification =====

Product ID:GENETRON 12

MSDS Date:01/01/1985

FSC:6830

NIIN:00-292-0147

MSDS Number: BDVPC

=== Responsible Party ===

Company Name:ALLIED CHEMICAL CORPORATION

Address:COLUMBIA RD & PARK AVE

Box:1087R

City:MORRISTOWN

State:NJ

ZIP:07960

Country:US

CAGE:1L168

=== Contractor Identification ===

Company Name:A

LLIED CHEMICAL COMPANY

Box:1087R

CAGE:1L168

Company Name:ALLIED-SIGNAL INC

Address:Box:2332R

City:MORRISTOWN

State:NJ

ZIP:07962-2332

Country:US

Phone:201-455-4414

CAGE:1L164

===== Composition/Information on Ingredients =====

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000

Fraction by Wt: 100%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ozone Depleting Chemical:1

===== Hazards Identificati

on =====

Effects of Overexposure:DEPRESSES CNS;IRRITATS RESPIR TRACT.HIGH CONCS CAUSE CARDIAC ARRYTHMIA,ASPHYXIATION AND DEATH.

===== First Aid Measures =====

First Aid:EYES:FLUSH W/WATER 15 MIN.SKIN:WASH W/SOAP & WATER.INHALED:REMOVE TO FRESH AIR,GIVE ART.RESP. IF NEEDED.DO NOT GIVE ADRENALIN NOR ANY STIMULANT.INGESTION:ITEM IS GAS A(AMBIENT TEMPERATURE:N/A.

===== Fire Fighting Measures =====

=====

Flash Point:NONE

Extinguishing Media:PRESENC IN FIRE DOES NOT HINDER USE OF ANY STANDARD MEDIUM.

Fire Fighting Procedures:SELF-CNTND BRTHG APP.H*2O TO DESPERSE VAPORS/COOL EXPOS CONT

Unusual Fire/Explosion Hazard:CONTACT W REACTV METALS(MOLTEN AL;BA/LI FINES)WILL PRODUCE RAPID EXOTHERMIC REACTIONS.

===== Accidental Release Measures =====

Spill Release Procedures:IF LARGE QUANTITY IS RELEASED,VACATE PREMISES AND ALLOW TO DISIPATE.NOTE TLV.

====

===== Handling and Storage =====

Handling and Storage Precautions:CONTACT OF COLD LIQUID WITH SKIN PRODUCE FROSTBITE.CONTACT WITH EYES.CAN CAUSE SERIOUS DAMAGE.AVOID EXCESS HEAT.OUTDOOR STORAGE PERMITTED.

Other Precautions:PROTECT FROM PHYSICAL DAMAGE.HALOCARBONS IN CLOSED/CONFINED AREAS REQUIRE WELL-VENTILATED DRAFT,AS THEY DEplete OXYGEN NECESSARY FOR BREATHING.

===== Exposure Controls/Personal Protection =====

Respiratory Pr

Protection:SELF-CONTAINED BREATHING APPARATUS IF NOT IN
WELL VENTILATED SPOT

Ventilation:MECHANICAL VENTILATION AS NEEDED.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

ITEM MEETS REQUIREMENTS FOR TYPE 12 UNDER FED SPEC BB-F-1421.

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-21.6

Vapor Pres:70

Vapor Density:4.28

Spec Gravity:1.32

Evaporation Rate & Reference:N/A(GAS)

Solubility in Water:SLIGHT

Appearance and Odor:COLORLESS LIQUEFIED GAS WITH FAINT ETHEREAL ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:DECOMPOSES AT GAS FLAME TEMPERATURE GIVE
HALOGEN,HALO-ACIDS

Hazardous Decomposition Products:TOXIC SUBSTANCES BY HIGH
HEAT,E.G.FLUORIDES,CARBONYL HALIDES

===== Disposal Considerations =====

Waste Disposal Methods:FOR

MODERATE QUANTITIES,PERMIT TO EVAPORATE IN
AIR AT SLOW RATE,SO AS NOT TO EXCEED TLV

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.