

AMERON PROTECTIVE COATIONS -- 37038 BLACK -- 8010-00-297-0547

===== Product Identification =====

Product ID:37038 BLACK

MSDS Date:01/01/1987

FSC:8010

NIIN:00-297-0547

MSDS Number: BDVXV

=== Responsible Party ===

Company Name:AMERON PROTECTIVE COATIONS

Address:201 N BERRY STREET

City:BREA

State:CA

ZIP:92621

Country:US

Info Phone Num:714-529-1951

Emergency Phone Num:714-529-1951

CAGE:0Y2E4

=== Contractor Identification ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

Box:1020

City:BREA

State:CA

ZIP:92622-1020

Country:US

Phone:714-529-1951

CAGE:0Y2E4

===== Composition/Information on Ingredients =====

Ingred Name:BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 37.2%

Other REC Limits:STEL 400 PPM

OSHA PEL:100 PPM

ACGIH TLV:300 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Report

s of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Explanation of Carcinogenicity:NONE

Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE  
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

===== First Aid Measures =====

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE  
CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A  
PHYSICIAN IF CONDITIONS PERSIST.

===== Fire Fighting Measures ==  
=====

Flash Point Method:TCC

Flash Point:86F

Lower Limits:1.1

Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE  
FIRES-FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON  
-SPARKING  
TOOLS

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE  
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE  
FLAMMABLES.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID  
FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR

SUPPLIED RESPIRATOR  
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY  
Supplemental Safety and Health  
RESPIRATOR USE BASED ON CHEM. CONC. AND CONDITIONS OF USE

===== Physical/Chemical Properties =====

HCC:F3  
Boiling Pt:B.P. Text:311-373F  
Vapor Density:>1  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:59.7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:AVOID FIRE,HEAT AND HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND  
FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants  
this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.