

PRAXAIR INC -- 27038-BLACK -- 8010-00-297-0591

===== Product Identification =====

Product ID:27038-BLACK

MSDS Date:01/01/1985

FSC:8010

NIIN:00-297-0591

MSDS Number: BDWBX

=== Responsible Party ===

Company Name:PRAXAIR INC

Address:39 OLD RIDGEBURY RD

City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Info Phone Num:203-794-5782

Emergency Phone Num:203-794-5782

CAGE:0LV01

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

S

tate:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

Company Name:PRAXAIR, INC.

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06810-5113

Country:US

Phone:800-772-9247; 800-PRAXAIR

CAGE:0LV01

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 45%

ACGIH TLV:500 PPM

===== Hazards Identification =====

Effects of Overexposure:IRRIT OF NOSE,THROAT,

EYES & POSS DIZZINESS &
NAUSEA.SPRAY MIST CONTN LEAD.

===== First Aid Measures =====

First Aid:INHAL:REMOVE FR EXPOSURE & PROVID FRESH AIR.SPLASH EYES-FLUSH
IMMED W/LG AMTS OF WATER FOR 15 MIN.SPLASH SKIN:REMOV CONTAM
CLOTHING & WASH ALL AFFECT AREA W/WATR.INGEST:DO NOT INDUC
VOMITNG.CONSULT A DR . IMMED IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point:104 F 40 C TCC
Extinguishing Media:CLASS B
EXTING, CARBON DIOXIDE, DRY CHEM OR ALCOHOL
FOAM
Fire Fighting Procedures:SELF CONTAINED BREATH APPARAT.WATER MAY BE
INEFFECTIVE.
Unusual Fire/Explosion Hazard:KEEP CONTNRS TIGHTLY CLOS.ISOLAT FR
HEAT,ELECTR EQPMT,SPARKS & OPN FLAME.DO NOT APPLY TO VRYHOT SUR

===== Accidental Release Measures =====

Spill Release Procedures:REMOV ALL SOURCES OF IGNIT (FLAMES,HOT
SURFACES,ELECTRICAL, STATIC OR FRICTIONAL SPARKS).VENTILAT AREA &
AVOID BREATHING VAPO
RS.REMOV W/ INERT ABSORB & NON-SPARKING
TOOLS.STEPS MUST BE TAKN TO PREVNT CONTAM OF GROUND WATR OR
STREAMS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOV 120 F.STORE LG
QUANTITIES IN COMPLIA W/OSHA 1910.106.CONTNRS SHLD BE CROUNDED &
BONDED TO THE RECEIVING CONTNR.
Other Precautions:DO NOT CUT OR WELD ON EMPTY CONTAINER. DO NOT USE
UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY
THE USER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY
WHN SPRAYING IN OURDR
Ventilation:PROVID GEN DILUT/LOC EXHAUST VENT TO KP CONCENT BELO ACEP
TL
Protective Gloves:SOLVENT,IMPERME
Eye Protection:SAFETY EYEWR
Other Protective Equipment:PROTECTV EQPMT TO PRVNT SKN CONTCT.SE
OSHA,29 CFR 1910.1025
Supplemental Safety and Health

===== Physical/Chemical Properties =====

=====

HCC:F4

Vapor Density:>AIR

Evaporation Rate & Reference: