

DEVOE & RAYNOLDS, INC -- MD-8733, GREEN PRIMER, MIL-P-24441/1 PART 1 -- 8010-00-437-6757

===== Product Identification =====

Product ID:MD-8733, GREEN PRIMER, MIL-P-24441/1 PART 1

MSDS Date:01/01/1987

FSC:8010

NIIN:00-437-6757

Kit Part:Y

MSDS Number: BDYXP

=== Responsible Party ===

Company Name:DEVOE & RAYNOLDS, INC

Address:2625 DURAHART ST

City:RIVERSIDE

State:CA

ZIP:92507-2606

Country:US

CAGE:EO559

=== Contractor Identification ===

Company Name:DEVOE & RAYNOL

DS CO, INC.

Box:7600

CAGE:EO559

Company Name:DEVOE COATINGS CO DIV OF GROW GROUP INC

Address:2625 DURAHART ST

Box:City:RIVERSIDE

State:CA

ZIP:92507-2606

Country:US

CAGE:70506

===== Composition/Information on Ingredients =====

Ingred Name:PIGMENTS

Fraction by Wt: 52.4%

Ingred Name:AMINO-AMIDE (VEHICLE)

Fraction by Wt: 19.5%

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 28.1%

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000

LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:INHAL: HEADACHE, NAUSEA, DIZ. SKIN: PRLNGD/RPTD  
CONTACT MAY CAUSE IRRIT. AVOID EYE CONTACT.

===== First Aid Measures =====

First Aid:SKIN: IMMEDIATELY FLUSH W/LARGE AMOUNTS OF WATER. REMOVE  
CONTAMINATED CLOTHING. EYE: IMMEDIATELY FLUSH W/WATER FOR AT LEAST  
15 MIN. CALL MD. INHAL: MOVE TO FRESH AIR.

===== Fire Fighting Measures =====

Flash Point:101 PMCC  
Lower Limits:1.4  
Upper Limits:11.2  
Extinguishing Media:CO\*2, DRY CHEMICAL  
Unusual Fire/Explosion Hazard:WATER SHOULD BE USED TO COOL CONTAINERS  
EXPOSED TO FIRE

===== Accidental Release Measures =====

Spill Release Procedures:AVOID BREATHING VAPORS, EXTINGUISH IGNITION  
SOURCES IN IMMEDIATE AREA. AVOID CONTACT W/LIQUID.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPERATURES.  
VENTILATION - USE SPARK PROOF EQUIPMENT.  
Other Precautions:CLOSE CONTAINERS AFTER USE. DOT CLASSIFICATION:  
FLAMMABLE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CONFINED AREAS - USE NIOSH/MSHA APPR RESPIRATOR  
DEVICE  
Ventilation:KEEP CONC BELOW TLV. ADEQUATE VENTILATION IS REQUIRED.  
Protective Gloves:SOLVNT RESIST  
Eye Protection:SOLVENT RESISTANT  
Other Protective Equipmen

t:NORMAL PROTECTIVE CLOTHING

Supplemental Safety and Health

PART A OF A TWO PART KIT, WHICH CONTAINS DIFFERENT CLASSES AND LABELS  
OF HAZARDOUS MATERIALS. 5 GAL. COMPONENT A.KEY1:F4.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:241 TO 246F

Vapor Pres:55

Vapor Density:2.55

Spec Gravity:1.39

Evaporation Rate & Reference:0.5 N-BUTYL ACET

Solubility in Water:MODERATE

Appearance and Odor:MOBILE, CONTAINING VOLATILE LIQS

Percent Volatiles by

Volume:48.1

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS, RUBBER SOFTENS.

Hazardous Decomposition Products:CO, CO\*2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN CLOSED CONTAINERS AWAY FROM  
IGNITION SOURCES. (MFG REC)

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of  
the Department

of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.