

SIDMAK LABORATORIES, INC -- N-1041 -- 8040-00-440-5603

===== Product Identification =====

Product ID:N-1041

MSDS Date:01/01/1987

FSC:8040

NIIN:00-440-5603

MSDS Number: BDYYN

=== Responsible Party ===

Company Name:SIDMAK LABORATORIES, INC

Address:17 WEST ST

Box:371

City:EAST HANOVER

State:NJ

ZIP:07936-2822

Country:US

Info Phone Num:201-386-0547

Emergency Phone Num:201-386-5566

CAGE:1BL76

=== Contractor Identification ===

Company Name:SHORE-UBS CHEMICAL CO INC

A

Address:100 MAIN ST

Box:City:ALLENHURST

State:NJ

ZIP:07711-1131

Country:US

Phone:201-531-7300

CAGE:31711

Company Name:SIDMAK LABORATORIES, INC

Address:17 WEST ST

Box:371

City:EAST HANOVER

State:NJ

ZIP:07936-2822

Country:US

Phone:201-386-5566

CAGE:1BL76

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENTS

Fraction by Wt: 78%

ACGIH TLV:78

Ingred Name:VEHICLE

Fraction by Wt: 12%

Ingred Name:ADDITIVES

Fraction by Wt: 6%

===== Hazards Identifi

cation =====

Effects of Overexposure:NARCOSSIS,STUPOR,DROWSINESS

===== First Aid Measures =====

First Aid:FRESH AIR AND/OR OXYGEN

===== Fire Fighting Measures =====

Flash Point:20F TOC -7C

Lower Limits:1.2

Upper Limits:7.0

Fire Fighting Procedures:CO\*2,POWDER CHEMICAL,TRICHLORETHANE

Unusual Fire/Explosion Hazard:AVOID CONTACT W/OXIDIZERS,OPEN  
FLAME,SPARKS,HOT SURFACES.

===== Accidenta

I Release Measures =====

Spill Release Procedures:APPLY DRI-RITE OR SPEED-DRY ABSORBENT  
MATERIALS TO SOAK UP LIQUID.

===== Handling and Storage =====

Handling and Storage Precautions:REASONABLE CAUTION TO AVOID CONTACT  
W/SLIN.STORE IN FLAMMABLE STORAGE AREA AT 60-90F.

Other Precautions:KEEP OUT OF DIRECT SUNLIGHT & IN SEALED CONTAINERS.

===== Exposure Controls/Personal Protection =====

Ventilation:LOC EXHAUST-PREVENT

VAPOR BUILD-UP,MECH-CROSS-VENTILATION

Protective Gloves:YES

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

PROCURED UNDER SHORE CHEMICAL 1041

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:138F 59C

Vapor Pres:100

Vapor Density:2.97

Spec Gravity:0.875

Evaporation Rate & Reference:TOLUENE -6

Appearance and Odor:OPAQUE CREAM COLOR,TOLUENE ODOR

Percent Volatiles by Volume:81.0

===== Stability and Reactivity Data ==

=====

Stability Indicator/Materials to Avoid: YES  
Stability Condition to Avoid: OXIDIZERS, OPEN FLAME, SPARKS, HOT SURFACES  
Hazardous Decomposition Products: CHLORINE, FORMALDEHYDE, AMMONIA

===== Disposal Considerations =====

Waste Disposal Methods: SOLVENT WASTE STEEL DRUM.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.