

SPRAYON PRODUCTS -- 208 CUTTING OIL -- 9150-00-450-6938

===== Product Identification =====

Product ID:208 CUTTING OIL

MSDS Date:01/14/1986

FSC:9150

NIIN:00-450-6938

MSDS Number: BDZDG

=== Responsible Party ===

Company Name:SPRAYON PRODUCTS

Address:26300 FARGO AVE

City:BEDFORD HEIGHTS

State:OH

ZIP:44146-1310

Country:US

Info Phone Num:214-292-7400

Emergency Phone Num:216-292-7400

CAGE:09800

=== Cont

ractor Identification ===

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

===== Composition/Information on Ingredients =====

Ingred Name:CUTTING FLUID

Fraction by Wt: 90.0%

Other REC Limits:5MG/CUM AS OIL MIST

Ingred Name:ISOBUTANE (PROPELLANT)

CAS:75-28-5

RTECS #:TZ4300000

Fraction by Wt: 5.0%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM

Ingred Nam

e:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 5.0%
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

===== Hazards Identification =====

Health Hazards Acute and Chronic:ACUTE:IRRITANT TO EYES,SKIN AND
RESPIRATORY TRACT;DIZZINESS OR NAUSEA. CHRONIC:BRAIN OR CNS DAMAGE
ON PROLONGED OR REPEATED CONTACT OR EXPOSURE.
Effects of Overexposure:EYES/SKIN:IRRITANT;INHAL:ANESTHETIC,IRRITNT TO
RESP.TRACT;HEADACHE,NAUSEA;INGEST:HARMFUL OR FATAL
Medical Con
d Aggravated by Exposure:NO DATA AVAILABLE

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:N/R,PROPELLANT
Lower Limits:1.8
Upper Limits:2.3
Extinguishing Media:CO*2,DRY CHE
MICAL OR FOAM.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.
Unusual Fire/Explosion Hazard:DO NOT SPRAY NEAR OPEN FLAME;KEEP AT ROOM
TEMPERATURE AS EXPOSUR. TO DIRECT SUNLIGHT MAY CAUSE BURSTG

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION:REMOVE ALL
SOURCES OF IGNITION;VENTILATE;AVOID BREATHING VAPORS AND REMOVE
WITH INERT ABSORBENT.

===== Handling and Sto

rage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.KEEP AT ROOM TEMPERATURE AND AWAY FROM HEAT, OPEN FLAMES AND SUNLIGHT.DO NOT PUNCTURE/INCINERATE;DO NOT SPRAY NEAR FIRE/FLAMES

Other Precautions:AVOID CONTACT WITH SKIN,EYES AND CLOTHES;DO NOT BREATHE VAPORS/MIST;KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE PEL/TLV

E PEL/TLV

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN 1.0 (ETHER=1)

Appearance and Odor:AEROSOL:CONTENTS UNDER PRESSURE

Percent Volatiles by Volume:10

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE NOTED

Stability Condition to Avoid:DO NOT STORE ABOVE 120F

Hazardous Decomposition Products:CO ,CO*2

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE;DIS

POSE OF IN ACCORDANCE WITH

LOCAL,STATE AND FEDERAL REGULATION:

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility

for the suitability of this information to their particular situation.