

PRATT & LAMBERT - WICHITA DIVISION -- 727-002 -- 8010-00-468-4204

===== Product Identification =====

Product ID:727-002

MSDS Date:01/01/1985

FSC:8010

NIIN:00-468-4204

MSDS Number: BDZNS

=== Responsible Party ===

Company Name:PRATT & LAMBERT - WICHITA DIVISION

Emergency Phone Num:316-733-1361

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

C

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

===== Composition/Information on Ingredients =====

Ingred Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

Fraction by Wt: 15.0%

OSHA PEL:0.1 MG/M3 (CRO3)

ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt: 25.0%

OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 8.0%
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 8.0%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:ALIPHATIC NAPHTHA
Fraction by Wt: 8.0%
ACGIH TLV:200 PPM

=====
= Hazards Identification =====

Effects of Overexposure:INHALED-ANESTHETIC, IRRITATE AIRWAY; SKIN/EYE
IRRITATION HEADACHE, DIZZINESS, COMA, CONFUSION.

===== First Aid Measures =====

First Aid:INCASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER
WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH
AIR, CALL A PHYSICIAN IF SYMPTONS PERSIST. PERFORM ARTIFICIAL
RESPIRATION IF BREATHING HAS STOPPED.

=====

===== Fire Fighting Measures =====

Flash Point:13 F, -11 C TCC

Lower Limits:0.9

Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL; POLYMER
FOAM-LARGE FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE
FOR FIREMEN

Unusual Fire/Explosion Hazard:PRESSURE BUILD-UP FROM EXTREME HEAT MAY
CAUSE EXPLOSION. USE WATER TO COOL CANS;FOR FIRE:FOGNOZZLES.

===== Accidental Release Measures =====

Spill Release Proc

edures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT
SURFACES, & ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA
CLASS ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions:DO NOT TAKE
INTERNALLY, CONTAINERS SHOULD BE GROUNDED
WHEN POURING, AVOID FREE FALL IN EXCESS OF A FEW INCHES, DO NOT
FLAME CUT, BRAZE, OR WELD COATED MATERIAL WITHOUT VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/ PROPER
FILTER OR HOOD.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY &
WELDING.

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protec

tive Equipment:PREVENT PROLONGED SKIN CONTACT TO
CONTAMINATED CLOTHING.

Supplemental Safety and Health

BAOILING RANGE 70-143 C. EACH FOLLOWING < 5 % BY WEIGHT: MEK, XYLENE,
TOLUENE, & VM&P NAPHTHA.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:175-290 F

Evaporation Rate & Reference:< ETHER

Percent Volatiles by Volume:71.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YE

S

Stability Condition to Avoid:FIRES, HEAT, & HOT SURFACES, SPARKS,
ELECTRICAL EQUIPMENT

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND
FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.