

DEFT CHEMICAL COATINGS -- 03-R-26 CATALYST,RED 11136,ISOCYANATE -- 8010-00-482-5649

===== Product Identification =====

Product ID:03-R-26 CATALYST,RED 11136,ISOCYANATE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-482-5649

Kit Part:Y

MSDS Number: BDZYJ

=== Responsible Party ===

Company Name:DEFT CHEMICAL COATINGS

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Emergency Phone Num:NONE

CAGE:EO418

=== Contractor Identification ===

Company Nam

e:DEFT CHEMICAL COATINGS

CAGE:EO418

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:BIURET OF 1,6 HEXAMETHYLENE DIISOCYANATE-SEE P/N IND "B"
FOR OTHER INGREDIENTS (NIOSH 1-5

Fraction by Wt: 30.0%

===== Hazards Identification =====

Effects of Overexposure:SKIN/EYES:IRRITATION;INH:IRRIT OF RESP

T

REACTION/ACUTE NERVOUS SYSTEM DEPRESSION;HEADACHE,DIZZINESS,ETC.

===== First Aid Measures =====

First Aid:EYES:FLUSH IMMEDIATELY WITH LARGE VOLUME OF WATER FOR AT LEAST 15 MIN.GET MEDICAL ATTENTION;SKIN:WASH AFFECTED AREA WITH WATER.REMOVE CONTAMINATED CLOTHING.GET MEDICAL ATTENTION IF IRRITATION OCCURS;INHALATION:REMOVE FROM EXPOSURE.RESTORE BREATHING BY CPR,KEEP WARM & QUIET.GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:20F(-6.6C)-TCC

Extinguishing Media:

CARBON DIOXIDE,FOAM OR DRY CHEM.(CLASS B FIRE EXTINGUISHER)

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS;WATER SPRAY TO COOL FIRE EXPOSED CONTAINER

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE IN HEAT OF FIRE;SPILL/RUNOFF MAY CAUSE POLLUTION,FIRE,&/OR EXPLOSION HAZARD

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES.VENTILATE AREA.USE PROTECTIVE EQUIPMENT.STOP LEAK WITHOUT RISK.Small Spill:CONTAIN/REMOVE WITH INERT ABSORBENT & NON-SPARKING TOOLS.PLACE IN COVERED CONTAINERS;Large Spill:DIKE AREA & PUMP LIQUID TO SALVAGE TANK.ABSORB REMAINING LIQUID & SHOVEL UP INTO CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW FIRE RISK AREA.DEEP CLOSURE TIGHT & CONTAINER UPRIGHT.STORE AWAY FROM PHYSICAL DAMAGE

Other Precautions:PREVENT PROLONGED/REPEATED BREATHING OF VAPOR OR SPRAY MIST.CAN CAUSE ALLERGIC REACTION.FOLLOW SPECIAL PRECAUTIONS TO APPLY ON HOT SURFACES.IF WATER IS USED FOR FIRE,FOG NOZZLES ARE PREFERABLE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR FOR PAINT,LAQUER,ENAMEL MISTS/ORGANIC VAPOR.

Ventilation:ADEQUATE USING EXHAUST FAN OR IAW 29CFR PART 1910.94

Protective Gloves:NEOPRENE/RUBBER

Eye Protection:SAFETY GLASS WITH SIDE SHIELD.

Other Protective Equipment:CLEAN,LONG SLEEVE/LONG LEG PROTECTIVE CLOTHING.

Supplemental Safety and Health

MSDS FM MFR DATED:10/28/80;TWO PART RESIN MODIFIED POLYURETHANE
COATING;SEE P/N IND "B" FOR OTHER INGREDIENTS OF THIS ITEM:SPEC REF
MIL-C-83286B,TYPE1.KEY1:F3.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175-313F

Vapor Density:>1.0

Spec Gravity:0.9023

Evaporation Rate & Reference: