

TECHALLOY MARYLAND INC, REID-AVERY DIV. -- MIL-11018-M WELDING ELECTRODE --
3439-00-486-8262

===== Product Identification =====

Product ID:MIL-11018-M WELDING ELECTRODE

MSDS Date:11/01/1985

FSC:3439

NIIN:00-486-8262

MSDS Number: BFBDP

=== Responsible Party ===

Company Name:TECHALLOY MARYLAND INC, REID-AVERY DIV.

Address:2310 CHESAPEAKE AVE.

City:BALTIMORE

State:MD

ZIP:21222-4012

Emergency Phone Nu

m:301-633-9300

CAGE:59711

=== Contractor Identification ===

Company Name:TECHALLOY COMPANY, INC.

Address:2310 CHESAPEAKE AVENUE

Box:City:BALTIMORE

State:MD

ZIP:21222

Country:US

Phone:410-633-9300; 800-638-1458

CAGE:59711

===== Composition/Information on Ingredients =====

Ingred Name:IRON

CAS:7439-89-6

RTECS #:NO4565500

Ingred Name:MANGANESE (SARA III)

CAS:7439-96-5

RTECS #:OO9275000

OSHA PEL:(C) 5 MG/M3 DUST

ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:SILICON

CAS:7440-21-3

RTE

CS #:VW0400000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CHROMIUM (SARA III)
CAS:7440-47-3
RTECS #:GB4200000
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)
CAS:1317-65-3
RTECS #:EV9580000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:NICKEL (SARA III
)
CAS:7440-02-0
RTECS #:QR5950000
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9192

Ingred Name:POTASSIUM TITANATE
CAS:12030-97-6

Ingred Name:SODIUM SILICATE
CAS:6834-92-0
RTECS #:VV9275000
ACGIH TLV:5 MG/CUM

Ingred Name:FELDSPAR
CAS:68476-25-5

Ingred Name:MOLYBDENUM
CAS:7439-98-7
RTECS #:QA4680000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3; 9293

Ingred Name:COLUMBIUM
CAS:7440-03-1
OSHA PEL:5 MG/CUM
ACGIH TLV:5 MG/CUM

Ingred Name:CALCIUM FLUORIDE
CAS:7789-75-5
RTECS #:EW1760000
OSHA PEL:2.5 MG/M3 (

F)
ACGIH TLV:2.5 MG/M3 (F); 8990

Ingred Name:ALUMINUM SODIUM FLUORIDE (SODIUM FLUOALUMINATE OR CRYOLITE)
CAS:15096-52-3
RTECS #:WA9625000
OSHA PEL:2.5 MG/M3 (F)
ACGIH TLV:2.5 MG/M3 (F); 8990

Ingred Name:CHROMIUM (III) OXIDE
CAS:1308-38-9
RTECS #:GB6475000
OSHA PEL:0.5 MG/M3 (CR)
ACGIH TLV:0.5 MG/M3 (CR); 8990

Ingred Name:POTASSIUM SILICATE
CAS:1312-76-1
ACGIH TLV:5 MG/CUM

Ingred Name:POTASSIUM HYDROXIDE (SARA III)
CAS:1310-58-3
RTECS #:TT2100000
OSHA PEL:C, 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9192

EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:ACUTE:MAY RESULT IN DISCOMFORT SUCH AS
DIZZINESS,NAUSEA,DRYNESS OR IRRITATION OF NOSE,THROAT OR
EYES,TIGHTNESS IN CHEST,FEVER & ALLERGIC REACTIONS. CHRONIC:MAY
LEAD TO SIDEROSIS & IS BELIEVED BY SOME INVESTIGATORS TO AFFECT

PULMONARY FUNCTION.

Explanation of Carcinogenicity:NICKEL & CHROMIUM ARE LISTED AS
CARCINOGENIC.

Effects of Overexposure:SEE "HEALTH HAZARDS".

Medical Cond Aggravated by Exposure:NONE STATED

=====
===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,ADMINISTER
OXYGEN,IF BREATHING HAS STOPPED,APPLY ARTIFICIAL RESPIRATOR; GET
MEDICAL HELP.

=====
===== Fire Fighting Measures =====

Extinguis

hing Media:USE PROPER MEDIA FOR SURROUNDING FIRE.
Fire Fighting Procedures:NEED TO WEAR PROTECTIVE EQUIPMENT.
Unusual Fire/Explosion Hazard:WELDING ARC & SPARKS CAN IGNITE
COMBUSTIBLES.

===== Accidental Release Measures =====

Spill Release Procedures:SWEEP UP OR SCOOP UP.

===== Handling and Storage =====

Handling and Storage Precautions:USE EXHAUST SYSTEM TO CLEAR WELDING
FUMES.

===== Exposure Controls/Personal
Protection =====

Respiratory Protection:USE RESPIRABLE FUME RESPIRATORY OR AIR SUPPLIED
RESPIRATOR WHEN WELDING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST
OR VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:USE ADEQUATE GENERAL VENTILATION & LOCAL EXHAUST AT THE
ARC.

Protective Gloves:WELDER'S GLOVES

Eye Protection:HELMET/FACE SHIELD WITH FILTER LENS.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING.

Supplemental Safety and Health

===== Physical/C
hemical Properties =====

HCC:N1

Solubility in Water:INSOLUBLE

Appearance and Odor:SOLID WIRE OR ROD.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:NONE STATED

Hazardous Decomposition Products:IT IS COMPLEX & CAN NOT BE CLASSIFIED
EASILY,DEPENDING ON THE ELECTRODE USED,COATING & CONTAMINANTS IN
THE ATMOSPHERE.

===== Disposal Con

siderations =====

Waste Disposal Methods:DISCARD ANY PRODUCT RESIDUE,DISPOSABLE CONTAINER
OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing
this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.