

CHEMRAY COATINGS CORPORATION -- TT-P-1757,COMP L, COLOR Y -- 8010-00-515-2208

===== Product Identification =====

Product ID:TT-P-1757,COMP L, COLOR Y

MSDS Date:01/01/1987

FSC:8010

NIIN:00-515-2208

MSDS Number: BFCBX

=== Responsible Party ===

Company Name:CHEMRAY COATINGS CORPORATION

Address:209 MICHIGAN AVE.

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Emergency Phone Num:201-245-1111

CAGE:OBRN9

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

Company Name:CHEMRAY COATINGS CORP.

Address:209 N. MICHIGAN AVE.

Box:NA

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:800-924-9300

CAGE:OBRN9

===== Composition/Information on Ingredients =====

Ingred Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

Fraction by Wt: 11.9%

OSHA PEL:0.1 MG/M3 (CRO3)

ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 5.1%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 22.3%

OSHA PEL:100 PPM

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 5.0%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 929

3

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 1.3%

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:EXCESSIVE INHALATION MAY CAUSE

HEADACHE,DIZZ,UNCONSC,COMA.SKIN/EYE CONTACT:PRIMARY IRRIT,DRY SKIN.

===== First Aid Measures =====

First Ai

d:INHALATN:REMOVE FROM EXPOSURE,RESTORE BREATHNG.KEEP WARM.CALL MD.EYES:IMMEDIATELY FLUSH W/WATER AT LEAST 15 MIN.CALL MD.
SKIN:REMOVE CONTAMINATED CLOTHING.WASH AFFECTED AREA W/SOAP & WATER.

===== Fire Fighting Measures =====

Flash Point:100F(38C) PMCC
Lower Limits:0.7
Upper Limits:6
Extinguishing Media:CO*2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:COOL CLOSED CONTAINERS W/WATER FOG.SELF-CNTND BREATHNG APP
Unusual Fire/Explosion Hazard:CLO
SED CONTAINERS MAY EXPLODE WHEN
EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE W/ABSORBENT MATERIAL OR FLUSH W/WATER INTO RETAINING AREA OR CONTAINER.AVOID SPARKS,FIRE & HOT SURFACES.VENTILATE AREA.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM HEAT,SPARKS,OR OPEN FLAME.USE W/ADEQUATE VENTILATION.AVOID PRO
LONGED OR REPEATED
CONTACT W/SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATORY PROTECTN FOR EXPOSURE OF CONCERN
Ventilation:LOCAL-KEEP BELOW TLV&LEL.MECH-EXPLOSION PROOF
Protective Gloves:YES
Eye Protection:GOGGLES
Other Protective Equipment:IMPERMEABLE APRON FOR PROLONGED OR REPEATED CONTACT.
Supplemental Safety and Health
PRODUCT ALSO CONTAINS 27% ALKYD RESIN,