

PENRECO DIVISION PENNZOIL -- PETROTECT AMBER, CODE 4040 -- 8030-00-526-1604
===== Product Identification =====

Product ID: PETROTECT AMBER, CODE 4040

MSDS Date: 01/01/1985

FSC: 8030

NIIN: 00-526-1604

MSDS Number: BFCLZ

=== Responsible Party ===

Company Name: PENRECO DIVISION PENNZOIL

Address: 700 MILIAM ST PENNZOIL PL

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

CAGE: JO941

=== Contractor Identification ===

Company Name: PENRECO DIVISION, PENNZOTL

Address: 700 MILIAM ST PENNZOIL PL

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

CAGE: JO941

Company Name: PENRECO, DIV OF PENNZOIL CO

Address: 700 MILIAM ST

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

Phone: 800-245-3952

CAGE: 86459

===== Composition/Information on Ingredients =====

Ingred Name: STODDARD SOLVENT

CAS: 8052-41-3

RTECS #: WJ8925000

Fraction by Wt: 58.5%

OSHA PEL: 500 PPM

ACGIH TLV: 100 PPM; 9293

=====

=====
Hazards Identification
=====

Effects of Overexposure:EYE: BURNING/IRRIT. SKIN: IRRIT/DERMATITIS.
INHAL: LOCAL IRRIT,DROW,COMA/PNEUMONIA(SEE SUP DATA)

=====
First Aid Measures
=====

First Aid:EYE:FLUSH W/WATER FOR AT LEAST 15 MIN.,CALL DOCTOR IMMED.
SKIN: REMOVE CONTAMINATED CLOTHING WASH EXPOSED AREA W/SOAP &
WATER,WASH CONTAMINATED CLOTHING BEFORE REUSE. INHAL: REMOVE TO FRESH
AIR IMMED.A PPLY ARTIFICIAL RESP IF
NEC (SEE SUP DATA)

=====
Fire Fighting Measures
=====

Flash Point:100F;38C;TCC
Lower Limits:1
Upper Limits:6
Extinguishing Media:CO*2,DRY CHEM,FOAM
Fire Fighting Procedures:USE WATER ONLY TO COOL CANS OF
FLAM/COMBUSTIBLE MATERIALS.
Unusual Fire/Explosion Hazard:CONTACT W/ ACID/ACID FUMES/HEATED TO
DECOMPOSITION WILL EMIT TOXIC FUMES OF SO*X

=====
Accidental Release Measures
=====

Spill Release Procedures:PROVIDE ADEQUATE VENT,REMOVE IGNITION
SOURCES,AVOID PROLONGED INHAL OF FUMES & LONG TERM SKIN
CONTACT,AVOID EYE CONTACT. FLUSH SPILL W/ WATER OR SWEEP UP W/
ABSORBENT MATERIAL;STORE IN COVERD METALLIC MARKED CANS & DISPOSE
AS SOON AS POSSIBLE.

=====
Handling and Storage
=====

Handling and Storage Precautions:FLAM & COMBUSTIBLE LIQUID KEEP AWAY
FROM SOURCES OF IGNITION. KEEP CANS CLOSED. PROVIDE ADEQUATE VENT.
USE IN ATMOSPHERE OF INERT GAS INSTEAD OF AIR.
Other Precautions:DO NOT TRANSFER TO UNMARKED CONTAINERS. CONTAINER: 55
GALLON.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPRVD RESP PROTECTION FOR PARTICULAR
EXPOSURE OF CONCERN
Ventilation:RECOMMENDED TO KEEP BELOW TLV.
Protective Gloves:RUBBER
Eye Protection:SFTY GOG W/FACE SHIELD.
Other Protective Equipment:RUBBER PRTECTIVE CLOTHING: BOOTS,APRONS;ETC.
Supplemental Safety and Health
SPEC: AM 2 GR4. EFFECTS OF OVEREXPOS

URE: INGEST: LOCAL IRRIT OF MUCOUS

MEMBRANES, MOUTH, THROAT, ESOPHAGUS, STOMACH. EMERGENCY PROCEDURE:

INGEST: DO NOT INDUCE VOMIT CALL DOCTOR IMMED.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300-325F

Vapor Pres: