

PENRECO DIVISION PENNZOIL -- PETROTECT AMBER, CODE 4040 -- 8030-00-526-1605

===== Product Identification =====

Product ID: PETROTECT AMBER, CODE 4040

MSDS Date: 01/01/1985

FSC: 8030

NIIN: 00-526-1605

MSDS Number: BFCMD

==== Responsible Party ====

Company Name: PENRECO DIVISION PENNZOIL

Address: 700 MILIAM ST PENNZOIL PL

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

CAGE: JO941

==== Contractor Identification ====

Company Name: PENRECO DIVISION, PENNZOTL

Address: 700 MILIAM ST PENNZOIL PL

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

CAGE: JO941

Company Name: PENRECO, DIV OF PENNZOIL CO

Address: 700 MILIAM ST

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

Phone: 800-245-3952

CAGE: 86459

===== Composition/Information on Ingredients =====

Ingred Name: STODDARD SOLVENT

CAS: 8052-41-3

RTECS #: WJ8925000

Fraction by Wt: 58.5%

OSHA PEL: 500 PPM

ACGIH TLV: 100 PPM; 9293

=====

===== Hazards Identification =====

Effects of Overexposure:EYE: BURNING/IRRIT. SKIN: IRRIT/DERMATITIS.  
INHAL: LOCAL IRRIT,DROW,COMA/PHEUMONIA (SEE SUP DATA)

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR AT LEAST 15 MIN,CALL DOCTOR IMMED.  
SKIN: REMOVE CONTAMINATED CLOTHING WASH EXPOSED AREA W/SOAP &  
WATER,WASH CONTAMINATED CLOTHING BEFORE REUSE. INHAL:REMOVE TO FRESH  
AIR IMMED.APP LY ARTIFICIAL RESP IF N  
EC (SEE SUP DATA)

===== Fire Fighting Measures =====

Flash Point:100F,38C; TCC

Lower Limits:1

Upper Limits:6

Extinguishing Media:CO\*2,DRY CHEM,FOAM

Fire Fighting Procedures:USE WATER ONLY TO COOL CANS OF  
FLAM/COMBUSTIBLE MATERIALS.

Unusual Fire/Explosion Hazard:CONTACT W/ACID/ACID FUMES/HEATED TO  
DECOMPOSITION WILL EMIT TOXIC FUMES OF SO\*X

===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE ADEQUATE VE  
NT,REMOVE IGNITION

SOURCES,AVOID PROLONGED INHAL OF FUMES & LONG TERM SKIN  
CONTACT,AVOID EYE CONTACT. FLUSH SPILL W/WATER OR SWEEP UP  
W/ABSORBENT MATERIAL;STORE IN COVERD METALLIC M ARDED CANS &  
DISPOSE AS SOON AS POSSIBLE.

===== Handling and Storage =====

Handling and Storage Precautions:FLAM & COMBUSTIBLE LIQUID KEEP AWAY  
FROM SOURCES OF IGNITION. KEEP CANS CLOSED. PROVIDE ADEQUATE VENT.  
USE ATMOSPHERE OF INERT GAS INSTEAD OF AIR.

Or

her Precautions:DO NOT TRANSFER TO UNMARKED CONTAINERS. CONTAINER:5  
GALLON.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESP PROTECT ON FOR PARTICULAR  
EXPOSURE OF CONCERN

Ventilation:RECOMMENDED TO KEEP BELOW TLV.

Protective Gloves:RUBBER.

Eye Protection:SFTY GOG W FACE SHIELD.

Other Protective Equipment:RUBBER PROTECTIVE CLOTHING:  
BOOTS,APRONS;ETC.

Supplemental Safety and Health

SPEC: AM 2 GR4. EFFECTS OF OVEREXPOSUR

E: INGEST: LOCAL IRRIT OF MUCOUS

MEMBRANES,MOUTH,THROAT,ESOPHAGUS,STOMACH EMERGENCY PROCEDURE:

INGEST: DO NOT INDUCE VOMIT CALL DOCTOR IMMED.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300-325F

Vapor Pres: