

ATLAS PAINT AND VARNISH COMPAY -- TT-E-489F, YELLOW #13538 (PAINT) -- 8010-00-527-2045

=====  
Product Identification  
=====

Product ID:TT-E-489F, YELLOW #13538 (PAINT)

MSDS Date:01/01/1987

FSC:8010

NIIN:00-527-2045

MSDS Number: BFCQZ

=== Responsible Party ===

Company Name:ATLAS PAINT AND VARNISH COMPAY

Emergency Phone Num:201-373-3300

CAGE:84239

=== Contractor Identification ===

Company Name:ATLAS P

AINT AND VARNISH CO

CAGE:84239

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALKYD RESIN

Fraction by Wt: 30%.

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 39%.

OSHA PEL:100 PPM

Ingred Name:LEAD COBALT DRIERS (OSHA PEL FROM 29CFR 1910.1025)

Fraction by Wt: 1%.

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.15 MG/M3(PB); 8990

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR

1910.1025),(CRO3 CEILING 0.1 MG

/M3)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 30%.

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

=====  
Hazards Identification  
=====

Effects of Overexposure:INHALATION: MILD DEPRESSION AND LOSS OF  
CONSCIOUSNESS IN HIGH CONCENTRATION.

=====  
First Aid Measures  
=====

First Aid:INHAL: REMOVE FROM EXPOSURE. CALL PHYSICIAN. SKIN: FLUSH WITH  
WATER. EYE: IMMEDIATELY FLUSH WITH WATER AT LEAST 15 MINUTES.

===== Fire Fighting Measures =====

Flash Point:108F TCC

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:CO\*2, FOAM, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:USE AIR SUPPLIED RESCUE EQUIP. COL EXPOSED  
CONTAINERS.

Unusual Fire/Explosion Hazard:USUAL HAZARD POTENTIAL BASED ON FLASH  
POINT.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP IMMEDIATELY AND DISCARD ABSORBANTS  
SAFELY. REMOV

E OPEN IGNITION. DIKE LARGE SPILLS AND PUMP INTO WASTE

TANK. KEEP VENTILATED AND AVOID PROLONGED BREATHING OF VAPORS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID OPEN FLAMES, SPARKS AND  
EXCESSIVE HEAT. VENTILATE AREA.

Other Precautions:READ LABEL REGARDING TOXICITY AND APPLICATION. DOT  
CLASSIFICATION - COMBUSTIBLE

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL - MOST DESIRABLE

Pr

otective Gloves:RECOMMENDED

Eye Protection:RECOMMENDED

Other Protective Equipment:CONVENTIONAL CLOTHES FOR PAINTING

Supplemental Safety and Health

MFG SUGGESTS TLV OF 200 PPM/8 HR WORK DAY

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:317 TO 388F

Vapor Pres:5

Vapor Density:4.8

Spec Gravity:1.2

Evaporation Rate & Reference:0.09 N-BU AC

Solubility in Water:NEGLIGIBLE

Appearance and Odor:MINERAL SPIRIT ODOR - THIN YELLOW PAINT

Percent Volatil

es by Volume:53.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
Stability Condition to Avoid: OPEN FLAME

===== Disposal Considerations =====

Waste Disposal Methods: SPECIAL HAZARDOUS WASTE CARRIER; EPA REGULATED -  
STATE OR FEDERAL.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.