

BONDED PRODUCTS,INCORPORATED -- EPI-SEAL UNIVERSAL RESIN,EPOXY,PART A --  
4730-00-542-3359

=====  
===== Product Identification =====

Product ID:EPI-SEAL UNIVERSAL RESIN,EPOXY,PART A

MSDS Date:01/01/1985

FSC:4730

NIIN:00-542-3359

Kit Part:Y

MSDS Number: BFDMC

=== Responsible Party ===

Company Name:BONDED PRODUCTS,INCORPORATED

Emergency Phone Num:215-696-9220

CAGE:DO082

=== Contractor Identification ===

Com

pany Name:BONDED PRODUCTS INCORPORATED (CANCELLED 19092 -NEW)

Address:439 S BOLMAR ST

Box:39

City:WEST CHESTER

State:PA

ZIP:19382-4933

Country:US

CAGE:3L885

Company Name:BONDED PRODUCTS, INC

Address:439 SOUTH BOLMAR STREET

Box:39

City:WEST CHESTER

State:PA

ZIP:19381-0039

Phone:610-696-9220 OR 215-739-9960

CAGE:DO082

=====  
===== Composition/Information on Ingredients =====

Ingred Name:PIGMENTS

Fraction by Wt: 19%

Ingred Name:VEHICLE (TYPE UNSPECIFIED)

Fraction by Wt: 76%

Ingred N

ame:FILLERS (TYPE UNSPECIFIED)

Fraction by Wt: 5%

=====  
Hazards Identification  
=====

Effects of Overexposure:HEADACHE,PRIMARY IRRIT TO SKIN EXPOSED ON PROLONG/REPEAT CONTACT.IRRITATING TO EYES.

=====  
First Aid Measures  
=====

First Aid:INHAL-REMOVE TO FRESH AIR.GIVE ARTIF RESP IF NOT BREATHING.  
SKIN-WASH THOROUGHLY WITH SOAP & WATER OR WATERLESS  
CLEANER.EYES-FLUSH W/WATER FOR 15 MIN.INGEST-INDUCE VOMITING.GET  
MEDICAL ASSISTANCE FOR ALL OF ABOVE EXPOSURES.

=====  
Fire Fighting Measures  
=====

Flash Point:>250 F  
Lower Limits:UNK  
Upper Limits:UNK  
Extinguishing Media:WATER SPRAY,FOAM,CARBON DIOXIDE,DRY CHEMICAL  
Fire Fighting Procedures:USE SELF CONTAINED BREATHING GEAR,STAY  
UPWIND,(SEE SUP DATA)  
Unusual Fire/Explosion Hazard:HANDLE AS COMBUSTIBLE MATERIAL

=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE DIKES TO  
CONTAIN.WEAR APPD RESPIR EQUIP &  
SKIN/EYE PROTECTION EQUIP.PUMP,SHOVEL OR SCRAPE INTO SALVAGE  
DRUMS.SOAK UP WITH ABSORBENT.GUARD AGAINST FIRE HAZARDS.REMOVE  
IGNITION SOURCES.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN TIGHTLY CLOSED CONTAINERS.USE  
ONLY WITH APPROVED CURING AGENT.WASH EXPOSED SKIN AFTER  
HANDLING.STORE IN COOL,DRY AREA.  
Other Precautions:REMOVE CONTAMINATED CLOTHES & LAUNDER BEFORE  
REUSE.D

ESTROY CONTAMINATED SHOES & LEATHER ARTICLES.USE RUBBER  
GARMETS.AVOID CONTACT WITH EYES,SKIN & CLOTHING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATORY EQUIPMENT  
Ventilation:LOCAL FOR MIXING AND IN APPLYING.HAVE VAPORS BLOWN AWAY.  
Protective Gloves:RUBBER  
Eye Protection:FACE SHIELD OR GOGGLES  
Other Protective Equipment:RUBBER GARMENTS,SAFETY SHOWER,EYE BATH  
Supplemental Safety and Health  
SPRAY WATER ON CONTAINERS EXPOSE  
D TO FIRE TO KEEP COOL.ITEM IS ASSEMBLY  
1 OF MIL-R-17882.KEY1:N1.

===== Physical/Chemical Properties =====

HCC:N1  
Boiling Pt:B.P. Text:>250 F  
Vapor Pres:UNK  
Vapor Density:UNK  
Spec Gravity:1.2  
Solubility in Water: