View NSN Online: https://aerobasegroup.es/nsn/8010-00-543-7839

## PRATT & LAMBERT-WICHITA DIV -- 793800 LAC SPRAYING CLEAR -- 8010-00-543-7839

Product ID:793800 LAC SPRAYING CLEAR

MSDS Date:01/01/1985

FSC:8010

NIIN:00-543-7839

MSDS Number: BFDRS === Responsible Party ===

Company Name: PRATT & LAMBERT-WICHITA DIV

Address:16116 E 13TH ST

Box:2153 City:WICHITA State:KS

ZIP:67201 Country:US CAGE:KO010

=== Contractor Identification =

==

Company Name: PRATT & LAMBERT-WICHITA DIV.

Box:2153 CAGE:KO010

Company Name: PRATT AND LAMBERT INC

Address:Box:6027 City:CLEVELAND

State:OH

ZIP:44101-1027 Country:US

Phone:216-566-2902

CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name: ISOBUTYL ACETATE

RTECS #:NP9100000 Fraction by Wt: 25% ACGIH TLV:150PPM

Ingred Name: ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000 OSHA PEL:100 PPM ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:5000 LBS

DOT Rpt Qty:500

Ingred Name: NAPHTHA ALIPHATIC

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Other REC Limits: NONE RECOMMENDED

**OSHA PEL:200 PPM** 

ACGIH TLV:200 PPM/300STEL;9394

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

========= Hazards Identification ================

Effects of Overexposure:INHAL:ANEST,IRRIT OR

RESPIR TRACT OR ACUT NERV

SYS DEPRESN, HDACH, DIZZ, CONFUS, UNCONSCIOUS, COMA.

First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE T FRESH AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST.

Flash Point:13F TCC-11C

Lower Limits:.90

Extinguishing Media: USE FIRE EXTING(CO\*2, DRY CHEM OR ALCOH

FOAM)LO


FIRE-POLYMER

Fire Fighting Procedures: SELF-CONTAINED BREATH APPARATUS SHLD BE AVAIL F/FIREMEN.

Unusual Fire/Explosion Hazard: KEEP CONTNRS TIGHTLY CLOS: ISOLAT FR HEAT, ELECTR EQPMT. SPARKS & OPEN FLAM. CLOS CONTNRS MAY EXPLO(SUP)

======== Accidental Release Measures ===========

Spill Release Procedures:REMOV ALL SOURCES OF IGNITION(FLAMES, HOT SURFACES, & ELECTRICAL, STATIC OR FRICTIONAL SPARKS)AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE W/INERT ABS



**ORBENT & NON-SPARKING** 

**REGULATIONS.INC** 

## INERATE IN APPRVD FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibilit

y for the suitability of this information to their particular situation.