

PPG INDUSTRIES, INCORPORATED (CHEMICAL DIVISION) -- HUB-THANE; PRODUCT CODE: 0330 --
6810-00-551-1487

===== Product Identification =====

Product ID:HUB-THANE; PRODUCT CODE: 0330

MSDS Date:11/01/1985

FSC:6810

NIIN:00-551-1487

MSDS Number: BFDZC

=== Responsible Party ===

Company Name:PPG INDUSTRIES, INCORPORATED (CHEMICAL DIVISION)

Address:ONE GATEWAY CENTER

City:PITTSBURGH

State:PA

ZIP:15222-1416

Country:US

Info Phone Num:304-843-1300

Emergency Phone Num:304-843-1300

CAGE:DO894

=== Contractor Identification ===

Company Name:PPG INDUSTRIES INC CHEMICAL DIVISION

Address:ONE GATEWAY CENTER

City:PITTSBURGH

State:PA

ZIP:15222-1416

Country:US

Phone:304-843-1300

CAGE:93915

Company Name:PPG INDUSTRIES, INC.

Address:4325 ROSANNA DR

Box:9

City:ALLISON PARK

State:PA

ZIP:15101

Country:US

Phone:412-592-5555

CAGE:DO894

===== Composition/Information on Ingredients =====

Ingred Name

:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 96.0%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemical:1

Ingred Name:1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA III)

CAS:123-91-1

RTECS #:JG8225000

OSHA PEL:S, 100 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:GLYCOL METHYLENE ETHER

CAS:646-06-0

RTECS #:JH6760000

Ingred Name:SEC-BUTYL ALC

OHOL (SARA III)

CAS:78-92-2

RTECS #:EO1750000

OSHA PEL:150 PPM

ACGIH TLV:100 PPM; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE: IRRITATION OF EYS, SKIN AND RESPIRATORY AND G. I. TRACTS; CNS EFFECTS, DIZZINESS, NAUSEA, HEADACHE, PULMONARY EDEMA, VOMITTING. CHRONIC: PULMONARY EDEMA, LIVER OR KIDNEY EFFECTS.

Effects of Overexposure:INHALATION: CNS DEPRESSIO

N, IRRITATION OF

RESPIRATORY TRACT, DIZZINESS, NAUSEA, LIGHT HEADEDNESS, HEADACHE, DEATH IF INHALED EXCESSIVELY. EYE/SKIN: DISCOMFORT, PAIN, IRRITATION OR DERMATITIS ON PRO LONGED CONTACT. INGESTION: IRRITATIONOF G. I. TRACT, PULMONARY EDEMA, VOMITING, ETC.

===== First Aid Measures =====

First Aid:EYES:IRRIGATION OF THE EYE IMMED. W/WATER FOR 5 MIN. IS GOOD SAFETY PRACTICE.SKIN:CONTACT WILL PROBABLY CAUSE NO MORE THAN IRRIT.WASH

OFF IN FLOWING WATER OR SHOWER. WASH CLOTHING. INHALATION: REMOVE TO FRESH AIR IF EFFECTS OCCUR. CALL PHYS AND/OR TRANSPORT

===== Fire Fighting Measures =====

Flash Point: NONE
Lower Limits: 7%
Upper Limits: 15%
Extinguishing Media: WATER, DRY CHEMICAL OR CARBON DIOXIDE
Fire Fighting Procedures: PRESSURE DEMAND SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard: NONE

===== Accidental Release Measures =====

Spill Release Procedures: USE APPROPRIATE SAFETY EQUIPMENT. SMALL LEAKS: MOP UP, WIPE UP, OR SOAK UP IMMEDIATELY. REMOVE TO OUT OF DOORS. LARGE SPILLS: EVACUATE AREA. CONTAIN LIQUID: TRANSFER TO CLOSED METAL CONTAINERS. KEEP OUT OF WATER SUPPLY.

===== Handling and Storage =====

Handling and Storage Precautions: HANDLE WITH REASONABLE CARE. AVOID BREATHING VAPOR. STORE IN COOL DRY PLACE. VAPORS OF THIS PRODUCT ARE HEAVIER THAN AIR & WILL COLLECT IN LOW AREAS SUCH AS PITS
Other Precautions: CONT'D (FROM PRECAUTIONS ABOVE) VAPOR OF THIS PRODUCT ARE HEAVIER THAN AIR & WILL COLLECT IN LOW AREAS SUCH AS PITS, DEGREASERS, STORAGE TANKS, & OTHER CONFINED AREAS. DO NOT ENTER THESE AREAS WHILE

===== Exposure Controls/Personal Protection =====

Respiratory Protection: APPROVED RESPIRATORY PROTECTION REQUIRED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL.
Ventilation: LOCAL EXHAUST-CONTROL OF VAPORS TO SUGGESTED GUIDE
Protective Gloves: NO SPECIFIC PROTECTION
Eye Protection: SAFETY GLASSES WITH/OUT

SIDE S

Other Protective Equipment: CARTRIDGE RESPIRATORS ARE NOT RECOMMENDED EXCEPT FOR EVACUATION

Supplemental Safety and Health

RESP PROTECT: APPROVED RESPIRATORY PROTECTION REQUIRED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. FOR EMERG. SELF-CONTAINED BREATHING APPARATUS RECOMMENDED.

===== Physical/Chemical Properties =====

HCC:T4

Boiling Pt: B.P. Text: 165F-74C

Melt/Freeze Pt: M.P/F.P Text: -49F/-45C

Vapor Pres: 135

Vapor Density: 4.54

Spec Gravity: 1.31 @

Evaporation Ra

te & Reference: 0.35 (ETHYL ETHER)

Solubility in Water: NEGLIGIBLE

Appearance and Odor: CLEAR COLORLESS LIQUID W/ETHER LIKE ODOR

Percent Volatiles by Volume: 100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

WATER-SLOW HYDROLYSIS PRODUCES CORROSIVE ACID

Stability Condition to Avoid: OPEN FLAMES, WELDING ARCS OR OTHER HIGH TEMP SOURCES WHICH IN

Hazardous Decomposition Products: HYDROGEN CHLORIDE & VERY SMALL AMTS OF PHOSGENE

& CHLORINE

===== Disposal Considerations =====

Waste Disposal Methods: IN SOME CASES, SMALL AMTS. MAY BE TRANSPORTED TO AN AREA WHERE IT CAN BE PLACED ON THE GROUND AND ALLOWED TO EVAPORATE SAFELY IF LOCAL, STATE, AND FEDERAL REGULATIONS PERMIT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expresses

ssly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.