

PRATT & LAMBERT - WICHITA DIVISION -- 793-102 -- 8010-00-577-4524

===== Product Identification =====

Product ID:793-102

MSDS Date:01/01/1985

FSC:8010

NIIN:00-577-4524

MSDS Number: BFFVB

==== Responsible Party ===

Company Name:PRATT & LAMBERT - WICHITA DIVISION

Emergency Phone Num:316-733-1361

CAGE:PRATT

==== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

C

ity:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt: 15.0%

OSHA PEL:150 PPM

ACGIH TLV:150 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

R

TECS #:NP9625000
Fraction by Wt: 8.0%
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ALIPHATIC NAPHTHA
RTECS #:SE7525000
Fraction by Wt: 8.0%
ACGIH TLV:200 PPM

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 15.0%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:SE75
55000
Fraction by Wt: 8.0%
OSHA PEL:100 PPM

===== Hazards Identification =====

Effects of Overexposure:INHALED:ANESTHETIC & IRRITATION TO AIRWAY.
IRRITATION TO SKIN AND EYES. HEADACHE, DIZZINESS, COMA

===== First Aid Measures =====

First Aid:IN CASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER
WHILE REMOVING CONTAM CLTHNG. IF INHALED, REMOVE TO FRESH AIR. CALL
MD IF SYMPTOMS PERSIST

=====

== Fire Fighting Measures =====

Flash Point:13F, -11C TCC

Lower Limits:0.9

Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL. POLYMER FOAM-LG FIRE

Fire Fighting Procedures:SELF-CONTAINED BRTHNG APPAR AVAIL FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE DUE TO PRESS BUILD UP. USE WATER TO COOL CLOSED CANS

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNIT ION (FLAMES, HOT

SURFACES AND ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID BRTHNG VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LG QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions:DO NOT TAKE INTERNALLY. AVOID FREE FALL IN EXCESS OF

A FEW INCHES. CONTAINERS SHOULD BE GROUNDED WHEN POURING. DO NOT FLAME CUT, BRAZE OR WELD COATED MATERIAL W/O VENTILATION

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER HOOD OR FILTER

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL WELDING&SAFETY

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH CONTAM

CLTHNG

Supplemental Safety and Health

BOILING RANGE 79-143C, CELLOSOLVE SOLVENT 15%, ISOPROPYL ALCOHOL