

SEAGRAVE COATING CORP CHEMRAY DIVISION -- F-120,MIL-P-L5930,VINYL CHROMATE PAINT --
8010-00-584-2953

===== Product Identification =====

Product ID:F-120,MIL-P-L5930,VINYL CHROMATE PAINT
MSDS Date:01/01/1985
FSC:8010
NIIN:00-584-2953
MSDS Number: BFGJY
=== Responsible Party ===
Company Name:SEAGRAVE COATING CORP CHEMRAY DIVISION
Address:209 N MICHIGAN AVE
City:KENILWORTH
State:NJ
ZIP:07033
Country:
US
Info Phone Num:201-245-1111
Emergency Phone Num:201-245-1111
CAGE:8D124
=== Contractor Identification ===
Company Name:SEAGRAVE COATING CORP CHEMRAY DIVISION
Address:209 N MICHIGAN AVE
Box:City:KENILWORTH
State:NJ
ZIP:07033
Country:US
Phone:201-245-1111
CAGE:8D124

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rp

t Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TRICRESYL PHOSPHATE 8W/VINYL CHLORIDE-VINYLACETATE
COPOLYMER THEY FORM 20% OF PRODUCT)
ACGIH TLV:0.1 MG/CUM

Ingred Name:VINYL CHLORIDE VINYL ACETATE COPOLYMER (W/TRICRESYL
PHOSPHATE THEY FORM 20% OF PRODUCT)
ACGIH TLV:0.1 MG/CUM

Ingred Name:ZINC CHROMATE
CAS:13530-65-9
RTECS #:GB3290000
OSHA PEL:0.1 MG/M3
(CRO3)
ACGIH TLV:0.01MG/M3(CR)A1;9192

===== Hazards Identification =====

Effects of Overexposure:MAY IRRIT SKIN/RESP SYS. OVER INH MAY CAUSE
LOWERING OF BODY TEMP, HEAT/RESP RATE.

===== First Aid Measures =====

First Aid:FLUSH EXPOSED SKIN FREELY W/WATER, CALL MD IF NEC. IF OVER
INH OCCURS, REMOVE TO WELL-VENT AREA.

===== Fire Fighting Measures =====

Flash Point:45F TOC
Lower L
imits:1.2
Upper Limits:7.5
Extinguishing Media:DRY CHEM, CO*2
Fire Fighting Procedures:WATER SPRAY MAY BE INEFF AS EXTINGUISHING
AGENT
Unusual Fire/Explosion Hazard:VAPORS CAN TRAVEL GREAT DISTANCE & FLASH
BACK TO ORIGIN

===== Accidental Release Measures =====

Spill Release Procedures:FOLLOW GEN CLEANING PROCEDURES. SM SPILLS MAY
BE WASHED AWAY W/WATER, MFR REC.

===== Handling and Storage =====

Handling and Storage Pr

Precautions:STORE IN COOL, DRY PLACE AWAY FROM
OPEN FLAMES & PHYSICAL ABUSE & W/GOOD VENT.

Other Precautions:ODOR THRESHOLD NOT SUFFICIENT TO WARN OF DANGEROUS
CONC. SECURE ALL SOURCES OF IGNITION. KEEP CNTNRS CLOSED AS MUCH AS
POSS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CNTND BRTHNG APPARATUS, NIOSH/MSHA APPRVD

Ventilation:USE LOCAL & MECH EXHST

Protective Gloves:YES

Eye Protection:YES

Supplemental Safety and Health

LMPBLCK,M

G-S10*4& ZN-CRO4 FORM 15%.AL STERATE