

PACIFIC AEROSOL,INC.2424 MERCED ST.,SAN LEANDRO CA -- 14064 -- 8010-00-584-3149

===== Product Identification =====

Product ID:14064

MSDS Date:01/01/1987

FSC:8010

NIIN:00-584-3149

MSDS Number: BFGNC

=== Responsible Party ===

Company Name:PACIFIC AEROSOL,INC.2424 MERCED ST.,SAN LEANDRO CA

Emergency Phone Num:415-351-4860

CAGE:34451

=== Contractor Identification ===

Company Name:AERVOE-PACIFIC CO, IN
C.

Address:1198 SAWMILL RD

Box:City:GARDNERVILLE

State:NV

ZIP:89410

Country:US

Phone:(702)-782-0100

CAGE:33451

Company Name:PACIFIC AEROSOL, INC.

CAGE:34451

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 19.0%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 45.0%

OSHA PEL:10

00PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SEC-BUTYL ACETATE (SARA III)
CAS:105-46-4
RTECS #:AF7380000
Fraction by Wt: 6.0%
OSHA PEL:200 PPM
ACGIH TLV:200 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 2.0%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 14.0%

===== First Aid Measures =====

First Aid:FUMES--MOVE AFFECTED TO FRESH AIR, RESTORE BREATHING, GET MEDICAL AID. EYE CONTACT--FLUSH THOROUGHLY WITH WATER, GET MEDICAL AID.

===== Fire Fighting Measures =====

Flash Point:-2.2F
Lower Limits:1.0
Extinguishing Media:CO2, DRY CHEMICAL OR FOAM
Fire Fighting Procedures:USE WATER SPRAY TO COOL CLOSED CONTAINERS EXPOSED TO HEAT
Unusual Fire/Explosion Hazard:KEEP FROM HEAT, SPARKS OR OPEN FLAME.CLOSED CNTAIN

ERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT OR
FIRE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION---VENTILATE AREA

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 120F. KEEP CONTAINERS AWAY
FROM HEAT AND OPEN FLAME

Other Precautions:AVOID INHALATION OF SPRAY MIST. DO NOT TAKE
INTERNALLY

===== Exposure Controls/Personal Protection
=====

Respiratory Protection:PAINT SPRAY MASK

Ventilation:PROVIDE VENTILATION TO KEEP VAPORS BELOW TLV.

Supplemental Safety and Health

TX2275000 PROPANE 14 PERCENT

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:-10F

Vapor Density:1+

Spec Gravity:0.9

Evaporation Rate & Reference:10

Solubility in Water:NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decom

position Products:CARBON MONOXIDE FUMES ON IGNITION

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL REGULATIONS. DO
NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be ac

curate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.