MANVILLE BUILDING MATERIALS CORPORATION -- FLEXIBLE MIN-K MID RANGE 2995-00-611-4422

Product ID:FLEXIBLE MIN-K MID RANGE MSDS Date:01/01/1985 FSC:2995 NIIN:00-611-4422 MSDS Number: BFHTW === Responsible Party === Company Name: MANVILLE BUILDING MATERIALS CORPORATION Emergency Phone Num: (303)978-3120 CAGE:1V185 === Contractor Identification === Company Name: MANVILLE BUILDING MATERIALS CORP. Box:5108 City:DENVER State:CO ZIP: 80217 Country:US Phone:303-978-3120 CAGE:1V185 Company Name:SCHULLER INTERNATIONAL INC. Address:Box:5108 **City:DENVER** State:CO ZIP:80217-5108 Country:US Phone:303-978-4900 CAGE:75165 Ingred Name: AMORPHOUS SILICA CAS#7631-86-9 Fraction by Wt: 60.0% ACGIH TLV:20 MPPCF Ingred Name: SILICA, CRYSTALLINE - QUARTZ CAS:14808-60-7 RTECS #:VV7330000 Fraction by Wt: 24.0% **OSHA PEL:SEE TABLE Z3** ACGIH TLV:0.1 MG/M3 RDUST;9293 Ingred Name:

INERT MINERAL FILLER Fraction by Wt: 16.0% ACGIH TLV:NOT SPECIFIED

==========

Ingred Name:GLASS OR QUARTZ CLOTH & THREAD Fraction by Wt: UNKN ACGIH TLV:NOT SPECIFIED

Effects of Overexposure:INHAL:MAY CAUSE UPPER RESPIRATORY IRRITATION DUE TO DUST.EYE:-TEMP.IRRITATION.SKIN:IRRITATION/RASH.

First Aid:INHAL:REMOVE TO FRESH AIR. EYES: FLUSH WITH LARGE QUANTITIES

OF WATER, CALL A PHYSICIAN IF NEEDED. SKIN: WASH EXPOSED AREAS WITH SOAP AND WARM WATER.

Flash Point:NON-FLAMMABLE Lower Limits:UNKN Upper Limits:UNKN Fire Fighting Procedures:NONE SPECIFIED BY THE MFR Unusual Fire/Explosion Hazard:NONE SPECIFIED

Spill Release Procedures: VACUUM CLEAN DUST. IF SWEEPING IS NECESSARY, USE DUST SUPPRESSANT.

Handling and Storage Precautions: USE NORMAL PROCEDURES FOR HANDLING & STORING. PROVIDE ADEQUATE VENTILATION. Other Precautions: AVOID INHALATION OF DUST. AVOID SKIN AND EYE CONTACT.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:DUST MASK/DUST RESPIR Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION Protective Gloves:OPTIONAL Eye Protection:GOGGLES Other Protecti ve Equipment:SAFETY SHOWER & EYE BATH Supplemental Safety and Health MSDS#IP 4650 M DATED 6/14/83

HCC:N1 Vapor Pres:UNK Vapor Density:UNKN Spec Gravity:0.26 Solubility in Water:NIL Appearance and Odor:QUILTED FLEXIBLE BLANKET - NO ODOR Percent Volatiles by Volume:UNKN

Stability Indicator/Materials to Avoid:YES HYDROFLUORIC ACID Stability Condition to Avoid: NONE SPECIFIED BY THE MFR. Hazardous Decomposition Products:NONE

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accu rate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.