Product ID:IB NO 220 MSDS Date:01/01/1987 FSC:8010 NIIN:00-616-9143 **MSDS Number: BFJBL** === Responsible Party === Company Name: ILLINOIS BRONZE POWDER AND PAINT COMPANY Address:300 EAST MAIN STREET **City:LAKE ZURICH** State:IL ZIP:60047-2580 Country:US Info Phone Num:312-488-8001 Emergency Phone Num:800-228-5635 CAGE:91794 === Contractor Identification === С ompany Name: ILLINOIS BRONZE PAINT COMPANY Address:300 EAST MAIN STREET **City:LAKE ZURICH** State:IL ZIP:60047-2580 Country:US Phone:800-228-5635 CAGE:91794 Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 Fraction by Wt: 11.1% OSHA PEL:100 PPM Ingred Name: METHYLENE CHLORIDE (SARA III) CAS:75-09-2 RTECS #:PA8050000 Fraction by Wt: 38.7% OSHA PEL:500 PPM/C,1000; Z2 ACGIH TLV:50 PPM, A2; 9192 EPA R

pt Qty:1000 LBS DOT Rpt Qty:1000 LBS
Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 Fraction by Wt: 1.5% OSHA PEL:100 PPM
======================================
Effects of Overexposure:INHALATION-ANESTHETIC;IRRITATION OF RESPIRATORY TRACT;DIZZINESS.SKIN OR EYE-PRIMARY IRRITATION
======================================
First Aid:FUMES-REMOVE FROM EXPOSURE,MOVE TO FRESH AIR.EYES-FLUSH WITH LA
RGE AMOUNTS OF WATER.FOR AT LEAST 15 MIN. CALL PHYSICIAN.SKIN-WIPE OFF WITH TOWEL.REMOVE REMAINDER WITH MINERAL SPIRITS OR LACQUER REMOVER.WASH WITH SOAP & WATER.
======================================
Flash Point:-40F,-40C Lower Limits:1.3% Extinguishing Media:NFPA CLASS B EXTINGUISHER Fire Fighting Procedures:WATER TO COOL CONTAINERS WEAR GOGGLES AND BREATHING APPARATU Unusual Fire/Explosion Hazard:CANS WILL RUPTURE AT 190F AND DISCHARGE FLAM MABLE CONTENTS
======================================
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT
======================================
Handling and Storage Precautions: DO NOT STORE ABOVE 120F STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA

QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS 1A FLAMMABLE LIQUIDS Other Precautions:DO NOT SPRAY IN EYES.DO NOT PU NCTURE OR INCINERATE CANS.DO NOT FLAME CUT,BRAZE OR WELD WITHOUT BUR. OF MINES APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE FOR CASUAL USE Ventilation:DILUTION OR EXHAUST TO KEEP BELOW TLV Protective Gloves:NONE Eye Protection:NO SPECIAL REQUIRED Supplemental Safety and Health B.P. RANGE 6-199C

HCC:F2 Boiling Pt:B.P. T ext:42-391F Percent Volatiles by Volume:89

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:HCL,CO,PHOSGENE

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.