

AMERICAN GAS & CHEMICAL CO, LTD. -- LEAK-TEC OX-65C -- 6850-00-621-1819

===== Product Identification =====

Product ID:LEAK-TEC OX-65C

MSDS Date:07/26/1991

FSC:6850

NIIN:00-621-1819

MSDS Number: BFJKF

=== Responsible Party ===

Company Name:AMERICAN GAS & CHEMICAL CO, LTD.

Address:220 PEGASUS AVE

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Info Phone Num:201-767-7300

Emergency Phone Num:201-767-7300

Preparer's Name:GEORGE KOSEL

CAGE:EO527

=== Contractor Id

entification ===

Company Name:AMERICAN GAS & CHEMICAL COMPANY LTD

Address:220 PEGASUS AVE

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Phone:201-767-7300/800-526-1008

CAGE:EO527

Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD

Address:220 PEGASUS AVENUE,

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Phone:201-767-7300

CAGE:03530

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt:

60.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 50 PPM
ACGIH TLV:C 50 PPM,VAPOR; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:SURFACTANT(S) - TYPE NOT SPECIFIED

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: MILD IRRITANT TO EYES AND SKIN.
CAN BE TOXIC IF INGESTED

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.
Effects of Overexposure:EYE AND SKIN IRRITATION.
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH WITH RUNNING WATER FOR AT LEAST 15
MINUTES WHILE LIFTING EYELIDS OPEN. IF IRRITATION DEVELOPS OR
PERSISTS, GET MEDICAL ATTENTION. SKIN:
WASH WITH SOAP AND PLENTY OF
WATER. IF IRRITATION DEVELOPS OR PERSISTS, GET MEDICAL ATTENTION.
VAPOR INHALATION UNLIKELY: REMOVE TO FRESH AIR. GET MEDICAL
ATTENTION IF REQUIRED. INGESTION: INDUCE VOMITING IMMEDIATELY. GET
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NONE
Autoignition Temp:Autoignition Temp Text:NONE
Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE
Fire Fighting Procedures:USE WATER T

O COOL FIRE-EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH WITH WATER. SOAK UP WITH ABSORBENT MATERIAL. DIKE TO CONTAIN MATERIAL AND PREVENT WATER POLLUTION.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AREA. KEEP CONTAINERS CLOSED AND PLAINLY LABELED.

Other Precautions:NONE

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:NONE NORMALLY REQUIRED.

Protective Gloves:NON-ABSORBENT GLOVES RECOMMENDED

Eye Protection:SAFETY GLASSES RECOMMENDED

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

CONTAINER LABELING USES

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM. THE LETTER "B" FOR PERSONAL PROTECTION MEANS THE USER SHOULD WEAR THE FOLLOWING WHEN WORKING WITH CHEMICAL: SAFETY GLASSES/SPLASH GOGGLES & GLOVES. HAZARDOUS INDEX UNDER THIS SYSTEM RATES DEGREE OF HAZARD FROM 0 TO 4 IN EACH CATEGORY: 0=MINIMAL;4=SEVERE

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:232F,111C

Melt/Freeze Pt:M.P/F.P Text:-65F,-54C

Vapor Pres:17.5

Vapor Density:0.6

Spec

Gravity:1.09

pH:6-7.5

Evaporation Rate & Reference: