

STANDARD INDUSTRIES -- RELIABLE NO. 24 (PRIOR TO 1/83,SEE ADD.DATA -- 6140-00-643-0495
===== Product Identification =====

Product ID:RELIABLE NO. 24 (PRIOR TO 1/83,SEE ADD.DATA

MSDS Date:01/01/1985

FSC:6140

NIIN:00-643-0495

MSDS Number: BFJSV

=== Responsible Party ===

Company Name:STANDARD INDUSTRIES

Address:NELSON RD AT RELIABLE DR

Box:27500

City:SAN ANTONIO

State:TX

ZIP:78227-0500

Country:US

CAG

E:32571

=== Contractor Identification ===

Company Name:STANDARD INDUSTRIES

Address:NELSON RD AT RELIABLE DR

Box:27500

City:SAN ANTONIO

State:TX

ZIP:78227-0500

Country:US

CAGE:32571

===== Composition/Information on Ingredients =====

Ingred Name:SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000

Fraction by Wt: 35%

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effe

cts of Overexposure:SPILLAGE ON BODY WILL CAUSE BURNS TO SKIN,
EYES, ETC.

===== First Aid Measures =====

First Aid:EYES- WASH WITH LARGE AMOUNT OF WATER. SKIN- WASH WITH LARGE
AMOUNT OF WATER. INTERNAL- TAKE LARGE QUANTITIES OF WATER OR MILK,
FOLLOW WITH MILK OF MAGNESIA. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Extinguishing Media:DRY CHEMICAL
Fire Fighting Procedures:WATER APPLIED MAY EVOLVE HEAT
& CAUSE
SPATTERING.

===== Accidental Release Measures =====

Spill Release Procedures:FLOOD WITH WATER. NEUTRALIZE WITH SODA ASH.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT SMOKE AROUND BATTERY- AS
HYDROGEN GAS IS EVOLVED FROM SULFURIC ACID.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE- UNDER NORMAL USAGE
Ventilation:MECHANICAL PREFERRED- ES
PECIALLY IF SPILLED
Protective Gloves:RUBBER
Eye Protection:GOGGLES
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:242 F
Vapor Pres:16
Spec Gravity:1.265
Solubility in Water:100%
Appearance and Odor:CLEAR LIQUID; NO APPRECIABLE ODOR.
Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZERS, CAUSTICS
Stability Condition to Avoi

d:SUB-ZERO TEMPERATURES

Conditions to Avoid Polymerization:AVOID SPILLAGE AS ACID IS CORROSIVE

===== Disposal Considerations =====

Waste Disposal Methods:NEUTRALIZE WITH SODA ASH. PLACE ABSORBED MATERIAL IN CONTAINER SUITABLE FOR SHIPMENT TO DISPOSAL AREA.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

ever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.