INDUSTRIAL RUBBER CEMENT CO. -- LOCK BOND -- 8040-00-656-0929 Product ID:LOCK BOND MSDS Date:01/01/1987 FSC:8040 NIIN:00-656-0929 MSDS Number: BFJZZ === Responsible Party === Company Name: INDUSTRIAL RUBBER CEMENT CO. Emergency Phone Num:213-333-4578 CAGE:55913 === Contractor Identification === Company Name: INDUSTRIAL RUBBER CEMENT CO Address:15257 E PROCTOR AVE Box:City:CITY OF INDUSTRY State:CA ZIP:91745-1019 Country:US CAGE :55913 ======= Composition/Information on Ingredients ======== Ingred Name:SOLVENTS Ingred Name: ETHYL ALCOHOL (ETHANOL) CAS:64-17-5 RTECS #:KQ6300000 Fraction by Wt: 10% OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192 Ingred Name: MINERAL SPIRITS CAS:64475-85-0 RTECS #:PY8240000 Fraction by Wt: 5% ACGIH TLV:500 =========== Hazards Identification ===============

Effects of Overexposure: ESSENTIALLY IDENTICAL TO GASOLINE IN IRRITATIVE & NARCOTIC ACTION

========

First Aid:INHALATION-REMOVE TO FRESH AIR. SKIN CONTACT-WASH W/ALCOHOL-FOLLOWED BY SOAP & WATER. EYE CONTACT-FLOOD W/LARGE QUANTITIES OF WATER. INGESTION-DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.
======================================
Flash Point:NONE Extinguishing Media:CO*2 & FINE SPRAY WATER
========= Accidental Release Measures ==========
Spill Release Procedu res:MATERIAL IS VERY VISCOUS & WILL NOT FLOW FROM OPEN CONTAINER. PICK UP W/SPATULA OR TROWEL.
======================================
Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION;STORE AT ROOM TEMPERATURE-OUT OF DIRECT SUNLIGHT IN VENTILATED AREA.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NOT NORMALLY REQUIRED Ventilation:LOC EXHAUST-GENERAL DILUTION VENTILATION SPECIAL-SUFFICIENT Protecti ve Gloves:KEEP OFF SKIN Supplemental Safety and Health
======================================
HCC:N1 Boiling Pt:B.P. Text:173F 78C Spec Gravity:1.38 Evaporation Rate & DAC 3.2 Solubility in Water:NEGLIGIBLE Percent Volatiles by Volume:10
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:DIRECT EXPOSURE TO HEAT OR FLAME Hazardous Decomposition Products:EMI

======= First Aid Measures ==========

TS DENSE ACRID SMOKE

======= Disposal Considerations ===========

Waste Disposal Methods: REPLACE TO SEALED CONTAINER, LANDFILL. REFER TO LOCAL DISPOSAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability fo

r its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.