View NSN Online: https://aerobasegroup.es/nsn/6810-00-664-0387 BRULIN & COMPANY, INC. -- SOLVENT 3812 -- 6810-00-664-0387 ============ Product Identification ========================= Product ID:SOLVENT 3812 MSDS Date:06/01/1990 FSC:6810 NIIN:00-664-0387 MSDS Number: BFKJV === Responsible Party === Company Name: BRULIN & COMPANY, INC. Address: 2920 DR ANDREW J BROWN AVE Box:270 City: INDIANAPOLIS State:IN ZIP:46206-0270 Country:US Info Phone Num:317-923-3211 Emergency Phone Num:317-923-32 33 CAGE:DO828 === Contractor Identification ===

====== Composition/Information on Ingredients ========

Ingred Name: METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III)

Company Name: BRULIN & COMPANY, INC.

Company Name: BRULIN AND CO INC

Address: 2920 DR ANDREW J BROWN AVE

Box:270-B

State:IN

Box:270

State:IN

City: INDIANAPOLIS

Phone:317-923-3211

City: INDIANAPOLIS

Phone:317-923-3211

RTECS #:KJ2975000

ZIP:46205-0270 Country:US

CAGE:94058

CAS:71-55-6

F

ZIP:46206-0270 Country:US

CAGE:DO828

ACGIH TLV:350 PPM/450STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1
========== Hazards Identification ============
Effects of Overexposure:BRIEF EXPOSURES: DIZZ,MILD SKIN & EYE IRRIT. (EXCESSIVE EXPOSURE).HDCH,DROW, (SEE SUPP DATA)
======================================
First Aid:EYES: FLUSH W/ WATER FOR 15 MIN. INHAL: REMOVE TO FRESH AIR. IF BREATH STOPS
GIVE ARTIFICIAL RESPIRATION. INGEST: INDUCE VOMIT. (ASPIRATION IS A HAZARD-GE MSDS-REF) CONSULT MD IF ANY SYMPTOMS PERSIST. (SKIN: WASH W/ WARM H*20 & SOAP,SEE MD-GE MSDS RE
======================================
Flash Point:NONE Lower Limits:7.5% Upper Limits:15% Extinguishing Media:WATER FOG. Fire Fighting Procedures:NIOSH/MSHA APPRVD PRESS DEMAND SCBA & FULL PROT EQUIP. Unusual Fire/Explosion Hazard:THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE HC L AND PHOSGENE.
========= Accidental Release Measures ==========
Spill Release Procedures:SMALL SPILLS: ABSORB ON SOLID ABSORBENT. LARGE SPILL: USE PROPER BREATH EQUIPMENT AND ABSORB ON SOLID ABSORBENT ALLOW TO EVAPORATE. KEEP OUT OF WATER SUPPLY AND INHABITED BUILDINGS.
=========== Handling and Storage =============

Handling and Storage Precautions:STORE IN CLOSED CONTAINERS IN A COOL, VENTILATED AREA. KEEP WATER-FREE.(GE-MSDS-REF).

raction by Wt: 100%

OSHA PEL:350 PPM/450 STEL

DO NOT SMOKE WHEN USING PRODUCT.

Other Precautions:PROVIDE MEDICAL MONITORING OF THOSE REGULARLY EXPOSED TO THIS PRODUCT IN THE WORKPLACE. PRECLUDE THOSE W/ CNS,LIVER,OR HEART DISEASE FROM EXPOSURE.(GE MSDS REF)

===== Exposure Controls/Personal Protection ========

Respiratory Protection:MFR RECMS NIOSH/MSHA APPRVD RESPIRATOR FOR CHLORINATED SOLVENTS.

Ventilation: MECHANICAL (GENERAL) SUFFICIENT TO KEEP BELOW TLV.

Protective Gloves: RECOMMENDED

Eye Protection: RECOMME

NDED

Other Protective Equipment: (AS REQUIRED TO PREVENT LIQUID CONTACT W/ SKIN-GE MSDS REF)

Supplemental Safety and Health

SPEC: TYPE I. OVEREXPOSURE: IMPAITED JUDGEMENT, UNCON, DERMAT, EYE IRRIT. GE MSDS REF) CONTAINER SIZE: 1 GAL CAN

======== Physical/Chemical Properties ==========

HCC:T4

Boiling Pt:B.P. Text:165F,74C Melt/Freeze Pt:M.P/F.P Text: