

PERMAGILE-SALMON LTD -- PG-2125,PART B -- 8030-00-670-8556

===== Product Identification =====

Product ID:PG-2125,PART B

MSDS Date:01/01/1985

FSC:8030

NIIN:00-670-8556

MSDS Number: BFLBB

=== Responsible Party ===

Company Name:PERMAGILE-SALMON LTD

Emergency Phone Num:516-349-1100

CAGE:HO069

=== Contractor Identification ===

Company Name:PERMAGILE INDUSTRIES INC

Address:101 COMMERCIAL STREET

City:PLAINVIEW

State:NY

ZIP:11803

Country:US

Phone:516-349-1100/800-424-

9300(CHEMTREC)

CAGE:13549

Company Name:PERMAGILE-SALMON LTD

CAGE:HO069

===== Composition/Information on Ingredients =====

Ingred Name:DIETHYLENE TRIAMINE

CAS:111-40-0

RTECS #:IE1225000

Fraction by Wt: 2%

OSHA PEL:1 PPM

ACGIH TLV:S, 1 PPM; 9192

Ingred Name:GLYCERIN

CAS:56-81-5

RTECS #:MA8050000

Fraction by Wt: 3%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 (MIST) 9293

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 4.5%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:2,4,6 TRI (DIMETHYLAMINO METHYL) PHENOL
CAS:90-72-2
RTECS #:SN3500000
Fraction by Wt: 14%

===== Hazards Identification =====

Effects of Overexposure:EYE/SKIN: IRRITATION. VAPORS:
HEADACHE,DIZZINESS

===== First Aid
d Measures =====

First Aid:EYE: FLUSH WITH WATER 15 MINUTES,GET MEDICAL ATTN. SKIN:
REMOVE CONTAMINATED CLOTHING & WASH AFFECTED AREA WITH SOAP &
WATER. INHALATION: REMOVE FROM EXPOSURE.

===== Fire Fighting Measures =====

Flash Point:>200F/93C (COC)
Extinguishing Media:CO*2,DRY CHEMICAL,WATER FOG,FOAM.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB SPILLAGE WITH RAGS,SAWDUST OR
SAND.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT AND OPEN FLAME.
USE ONLY WITH ADEQUATE VENTILATION.
Other Precautions:AVOID BREATHING VAPORS AND EYE/SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN.
Ventilation:LOCAL/MECHANICAL
Protective Gloves:RUBBER/PLASTIC
Eye Protection:SAFETY GLA

SSES/GOGGLES

Other Protective Equipment:COVERALLS OR APRON.

Supplemental Safety and Health

ADD INGREDIENTS: FUMED SILICA, 3%;MAGNESIUM SILICATE, 28%;POLYAMIDE
RESIN, 39%;IRONOXIDE BLACK, 1.5%. PART B OF A TWO PART KIT.

CONTAINER SIZE: 4 LB. TYPE 1 KEY1:N1.

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:1.18

Evaporation Rate & Reference: