

PRATT & LAMBERT -- PO BLUE -- 8010-00-733-2196

=====  
Product Identification  
=====

Product ID:PO BLUE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-733-2196

MSDS Number: BFMSL

=== Responsible Party ===

Company Name:PRATT & LAMBERT

Emergency Phone Num:316-733-1361

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Countr

y:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 60%

ACGIH TLV:500 PPM

Ingred Name:METHYL ETHYL KETOXIME

RTECS #:PM7783000

Fraction by Wt: 5%

ACGIH TLV:0.500 G/KG

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fractio

n by Wt: < 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SILICA, CRYSTALLINE - QUARTZ  
CAS:14808-60-7  
RTECS #:VV7330000  
Fraction by Wt: < 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:SEE TABLE Z3  
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:MINERAL SPIRITS (VP 2 MM HG @ 20C)  
CAS:64475-85-0  
RTECS #:PY8240000  
Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/525 MG/CU.M.  
ACGIH TLV:100 PPM/525 MG/CU.M.

Ingred Name:METHYL ISOAM  
YL KETONE  
CAS:110-12-3  
RTECS #:MP3850000  
Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM; 9293

Ingred Name:ETHYL BENZENE (SARA III)  
CAS:100-41-4  
RTECS #:DA0700000  
Fraction by Wt: < 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/125 STEL  
ACGIH TLV:100 PPM/125STEL 9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 10%  
Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:VOC 3.19 LB/GAL LESS WATER & NEGLIGIBLY PHOTOCHEMICALLY  
REACTIVE MATERIALS 383 G/L LESS WATER

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC 5.87 LB/GAL SOLIDS 704 G/L SOLIDS

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Effects of Overexposure:IRRIT OF NOSE,THROAT,EYES & POSS DIZZINESS &  
NAUSEA.SPRAY MISTCONTN LEAD.

=====  
First Aid Measures  
=====

First Aid:INHAL:REMOVE FR EXPOSUR & PROVID FRESH AIR.SPLASH EYES-FLUSH  
IMMED W/LG AMTS OF WATER FOR 15 MIN.SPLASH SKIN:REMOV CONTAM  
CLOTHING & WASH ALL AFFECT AREA W/WATR.INGEST:DO NOT INDUC  
VOMITNG.CONSULT A DR . IMMED IN ALL CASES.

=====  
Fire Fighting Measures  
=====

Flash Point:104 F 40 C TCC

Extinguishing Media:CLASS B EXTING, CARBON DIOXIDE,  
DRY CHEM OR ALCOHOL  
FOAM

Fire Fighting Procedures:SELF CONTAINED BREATH APPARAT,WATER MAY BE  
INEFFECTIVE.

Unusual Fire/Explosion Hazard:KEEP CONTNRS TIGHTHLY CLOS.ISOLAT FR  
HEAT,ELECTR EQPMT,SPARKS & OPN FLAME.DO NOT APPLY TO VRYHOT SUR

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOV ALL SOURCES OF IGNIT (FLAMES,HOT  
SURFACES,ELECTRICAL, STATIC OR FRICTIONAL SPARKS).VENTILAT AREA &  
AVOID BREATHING VAPORS.REMOV W/ INERT ABSORB

& NON-SPARKING

TOOLS. STEPS MUST BE TAKN TO PREVNT CONTAM OF GROUND WATR OR STREAMS.

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE ABOVE 120 F. STORE LG QUANTITIES IN COMPLIA W/OSHA 1910.106. CONTNRS SHLD BE GROUNDED & BONDED TO THE RECEIVING CONTNR.

Other Precautions: DO NOT CUT OR WELD ON EMPTY CONTAINER. DO NOT USE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER.

=====

Exposure Controls/Personal Protection =====

Respiratory Protection: NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY WHN SPRAYING IN OUTDR

Ventilation: PROVID GEN DILUT/LOC EXHAUST VENT TO KP CONCENT BELO ACEP TL

Protective Gloves: SOLVENT, IMPERME

Eye Protection: SAFETY EYEW

Other Protective Equipment: PROTECTV EQPMT TO PRVNT SKN CONTCT. SE OSHA, 29 CFR 1910.1025

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt: B.P. T

ext: 311-373F

Vapor Density: >AIR

Evaporation Rate & Reference: