

WITCO CHEMICAL CORP,SOUTHWEST PETRO-CHEM -- SA 827 3149,MIL-L-46000B --
9150-00-753-4686

===== Product Identification =====

Product ID:SA 827 3149,MIL-L-46000B

MSDS Date:01/01/1985

FSC:9150

NIIN:00-753-4686

MSDS Number: BFNBX

=== Responsible Party ===

Company Name:WITCO CHEMICAL CORP,SOUTHWEST PETRO-CHEM

Emergency Phone Num:(913) 782-5800

CAGE:1F469

=== Contractor Identification ===

Company Name:E

XXON CO USA-SOUTHWEST GREASE BUSINESS UNIT

Address:1400 S HARRISON

Box:1974

City:OLATHE

State:KS

ZIP:66061

Country:US

Phone:913-656-3701/800-424-9300(CHEMTREC)

CAGE:70878

Company Name:WITCO CHEMICAL CORP GOLDEN BEAR OIL CO DIVISION

Address:MANOR & NORRIS ROADS

Box:5446

City:OILDALE

State:CA

ZIP:93388-5446

Country:US

Phone:805-393-7110/800-424-9300(CHEMTREC)

CAGE:1F469

===== Composition/Information on Ingredients =====

Ingred Name:LITHIUM STEARATE (SPECIFICATION REQUIRES 8.0%

+ OR - 0.3)

CAS:4485-12-5

RTECS #:WI4370000

Ingred Name:BIS (2-ETHYLHEXYL) SEBACATE (SPECIFICATION REQUIRES 89.0% +

OR - 1.0)

CAS:122-62-3

RTECS #:VS1000000

Ingred Name:DIISOPROPYL PHOSPHITE (SPECIFICATION REQUIRES 1.0% + OR -

0.2)

CAS:1809-20-7

RTECS #:SZ7660000

Ingred Name:2,6-DI-TERT-BUTYL-P-CRESOL

CAS:128-37-0

RTECS #:GO7875000

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3; 9192

==== Hazards Identification =====

Effects of Overexposure:SKIN IRRIT ON PROLONGED CONTACT.SEVERE EYE BURNS. MAY CAUSE RESP IRRIT,DIZZ,NAUSEA & LOSS OF CONSCSN

==== First Aid Measures =====

First Aid:FLUSH EYES IMMEDIATELY W/WATER @ LEAST 15 MIN.CALL MD IMMEDIATELY. WASH SKIN THOROUGHLY W/SOAP & WATER. IF OVERCOME BY VAPORS,MOVE FROM CONTAMINATED AREA.IMMED CALL MD. IF INGESTED,DO NOT INDUCE VOMIT ING.CALL MD IMMEDIATELY.

==== Fire Fighting Measures =====

Flash Point:172F,78C COC
Extinguishing Media:DRY CHEM,CO*2,FOAM,WATERFOG,SAND & EARTH
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.
Unusual Fire/Explosion Hazard:DENSE SMOKE

==== Accidental Release Measures =====

Spill Release Procedures:TRANSFER BULK OF MATERIAL INTO ANOTHER CONTAINER. ABSORB REMAINDER W/PROPER ABSORBENTS SUCH AS SAND,EARTH,VERMIC ULITE.SWEEP UP AND DISPOSE AS SOLID WASTE IN ACCORDANCE W/LOCAL,STATE & FEDERAL REGULATIONS.

==== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED.AVOID CONTACT W/SKIN,EYES & CLOTHING.WASH THOROUGHLY AFTER HANDLING.WASH CLOTHING BEFORE REUSE.
Other Precautions:KEEP AWAY FROM FEED AND FOOD PRODUCTS.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:MFR STATES NONE REQUIRED
Ventilation:GENERAL MECHANICAL
Protective Gloves:OIL RESISTANT
Eye Protection:SFTY GOGS/FULL FACE SHLD
Other Protective Equipment:RUBBER OR PLASTIC GLOVES ARE SUITABLE
Supplemental Safety and Health
OIL-FREE BARIUM PETROLEUM SULFONATE W/AVG MOLECULAR WGT OF > 1090 IS ACCEPTABLE IN LIEU OF BARIUM DINONYLNAPHTHALENE SULFONATE. BOILING PT BASED ON DIISOPROPYL PHOSPHATE.

==== Physical/Chemical Properties =====

HCC:V4
Boiling Pt:B.P. Text:160F
Spec Gravity:0.

921
Solubility in Water:SLIGHT
Appearance and Odor:AMBER VISCOUS LIQUID W/BLAND ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS SUCH AS:CHROMIC ACID,BROMINE,HYDROGEN PEROX
Hazardous Decomposition Products:CO,CO*2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL,STATE,AND FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.