

U.S. ARMY ARMAMENT, MUNITIONS & CHEMICAL COMMAND -- DECONTAMINATING AGENT DS2 --
6850-00-753-4870

===== Product Identification =====

Product ID:DECONTAMINATING AGENT DS2

MSDS Date:09/28/1984

FSC:6850

NIIN:00-753-4870

MSDS Number: BFNDW

=== Responsible Party ===

Company Name:U.S. ARMY ARMAMENT, MUNITIONS & CHEMICAL COMMAND

Address:ATTN: SMCCR-SFS. HDQ, BLDG E5101

City:ABERDEEN PROVING GROUND

State:

MD

ZIP:21010-5423

Country:US

Info Phone Num:301-278-5201 (AFTER DUTY HOURS)

Emergency Phone Num:301-671-4411 (0800-1630 EST)

CAGE:80706

=== Contractor Identification ===

Company Name:POLY RESEARCH CORPORATION

Address:125 CORPORATE DRIVE

Box:City:HOLTSVILLE

State:NY

ZIP:11742-2007

Country:US

Phone:516-758-0460

CAGE:64713

Company Name:U.S. ARMY ARMAMENT, MUNITIONS & CHEMICAL COMMAND

Address:ATTN: SMCCR-SFS. HDQ, BLDG E5101

Box:City:ABERDEEN PROVING GROUND

State:MD

ZIP:21010-5423

Country:US

Phone:3

01-671-4411 (0800-1630 EST)

CAGE:80706

===== Composition/Information on Ingredients =====

Ingred Name:DIETHYLENE TRIAMINE

CAS:111-40-0

RTECS #:IE1225000

Fraction by Wt: 69.-71%.

OSHA PEL:1 PPM

ACGIH TLV:S, 1 PPM; 9192

Ingred Name:2-METHOXYETHANOL (EGME) (SARA III)

CAS:109-86-4

RTECS #:KL5775000

Fraction by Wt: 27.-29%.

OSHA PEL:S, 25 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:SODIUM HYDROXIDE (SARA III)

CAS:1310-73-2

M3
ACGIH TLV:C 2 MG/M3; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingrid Name:MATERIAL MANUFACTURED FOR ARMY I/A/W THE REQMTS OF SPEC.;
ARMY'S CHEM. RES. & DEV. CTR. PROVIDED THE MASTER MSDS!
RTECS #:9999999ZZ

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: CORROSIVE TO TISSUE & HIGHLY
IRRITANT TO RESPIRATORY TR
ACT; CHRONIC: REPEATED EXPOSURE TO
"DETA" CAN CAUSE SKIN SENSITIZATION & ASTHMA; SUFFICIENT EXPOSURE
TO "EGME" MAY CAUSE "CNS" DEPRESSION & LIVER DAMAGE. ALTHOUGH NOT
DEFINITELY ESTABLISHED IN HUMANS, REPRODUCTIVE EFFECTS ARE ALSO A
MAJOR CONCERN.
Effects of Overexposure:NO TOX. DATA AVAILABLE ON DS2. HOWEVER, DS2:
ALKALI WHICH ON CONTACT WILL CORRODE TISSUE. EFFECTS EXHIBITED ARE
A FUNCTION OF ROUTE OF EXPOS., AMT. OF SUBST. PRESENT & DURATION OF
EXPOSURE; HEALTH E
FF ECTS RANGE FROM MILD BURNS & PRIMARY
IRRITATION TO CORNEAL OPACIFICATION,SEVERE BURNS, NAUSEA,
VOMITING(SEE SUPPL DATA)
Medical Cond Aggravated by Exposure:PRE-EXISTING RESPIRATORY
CONDITIONS.

===== First Aid Measures =====

First Aid:SKIN: FLUSH AWAY W/WATER UNTIL "SOAPINESS" IS NO LONGER
PRESENT; EYES: IMMEDIATELY FLUSH W/COPIOUS AMTS. OF WATER FOR AT
LEAST 15 MINS. IN EITHER CASE, SEEK MEDICAL ATTN.; INHAL: REMOVE TO
FRESH AIR
- GIVE CPR/O*2 AS SITUATION DICTATES. ADDITIONAL
SUPPORTIVE MEASURES MAY BE REQUIRED; INGEST: IF CONSCIOUS, GIVE
PATIENT AS MUCH MILK OR WATER AS POSSIBLE. DO NOT INDUCE VOMITING.
GET MED. ATTN. IMMED.

===== Fire Fighting Measures =====

Flash Point:168F/75.6C
Extinguishing Media:CARBON DIOXIDE, ALCOHOL FOAM, WATER
Fire Fighting Procedures:NONE CITED
Unusual Fire/Explosion Hazard:NEVER MIX OR STORE ACIDS, OXIDIZING
AGENTS, OR STB(SUPER-TROPICAL

BLEACH) TOGETHER W/ DS2; FIRE OR
EXPLOSION MAY RESULT.

===== Accidental Release Measures =====

Spill Release Procedures:SPILLS ON POROUS SURFACES(CONCRETE, WOOD,
ETC.) SHOULD BE CLEANED & NEUTRALIZED IMMEDIATELY. OTHERWISE, IT
WILL BE ABSORBED & BECOME AN INDEFINITE HAZARD. CONTAIN SPILL,
NEUTRALIZE, ABSORB ON VERMICULITE, CLAY OR DIATOMACEOUS EARTH.
SCOOP UP IN DRUM!

Neutralizing Agent:SODIUM BISULFATE

===== Handling and Storage
=====

Handling and Storage Precautions:AVOID EXTREME TEMPERATURES(I.E.,
160F/71C) FOR STORAGE! AVOID CONTACT W/LEAKING LIQUID OR VAPOR.
Other Precautions:SPILL/RELEASE PROCEDURE CONTD: SCOOP UP MATERIAL &
CONTAMIN. MATTER, PLACE IN EPOXY COATED DRUM W/REMOVABLE HEAD IAW
EPA & DOT RQMTS.; DURING CLEAN-UP,WEAR FULL FACE RESPIR. W/ORGANIC
VAPOR CARTRIDGE, ARM-LENGTH RUBBER GLOVES & RUBBER APRON.

===== Exposure Controls/Personal Protection =====
=====

Respiratory Protection:FOR DS2 AIRBORNE CONC. 5 PPM OR EMERGENCIES, USE "SCBA"
Ventilation:LOCAL EXHAUST: NECESSARY IF TLV(TWA) EXCEEDED.
Protective Gloves:BUTYL RUBBER: ARM'S LENGTH TYPE
Eye Protection:SPLASHPROOF GOGGLES /FULL FACE SHIELD
Other Protective Equipment:AS REQUIRED FOR TASK AT HAND; CORROSIVE
RESISTANT(I.E. RUBBER) GAUNTLET, BOOTS, & APRON.
Work Hygienic Practices:USE MATERIAL IAW THE GUIDLINES & INSTRUCTIONS
SET FORTH IN USER'S TECH MANUAL.
Supplemental Safety and Health
SIGNS & SYMPTOM OVEREXP. CONTD: RESPIRATORY IRRITATION, SKIN
SENSITIZATION.

===== Physical/Chemical Properties =====

HCC:B1
Boiling Pt:B.P. Text:380F/193.3C
Spec Gravity:0.97 - 0.98
pH:>12.5
Appearance and Odor:CLEAR AMBER SOLUTION WITH AMMONIA-LIKE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
CORROSIVE: INCOMPATIBLE W/AL,CD,SN, & ZN; LEXAN,CELLULOSE
ACETATE,PVC,MYLAR,ACRYLIC;PAINT,

WOOL,OXIDIZING MATRL

Stability Condition to Avoid:EXPOSURE TO AIR. DS2 WILL DETERIORATE IN
AIR. EXPOSURE OF 48 HRS OR MORE TO OPEN AIR PRODUCES GELATIN-LIKE
BODIES!

Hazardous Decomposition Products:NONE CITED

===== Disposal Considerations =====

Waste Disposal Methods:CHOICE OF METHOD DEPENDS ON PHYSICAL CONDITION
OF WASTE & FACILITY'S CAPABILITY. FOR EXCESS STOCK,COORDINATE
W/LOCAL DRMD; OVERSEAS OPERATE W/IN HOST COUNTRY & DRMD
REGS.;/WASTE
CORROSIVE(PH >12.5) W/ EPA HAZ. WASTE:D002; INCINERATE
OR NEUTRALIZE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsi
bility for the suitability of this information to their
particular situation.