View NSN Online: https://aerobasegroup.es/nsn/8030-00-753-5005

GOAL CHEMICAL SEALANTS CORP. -- GC-408 CLASS B -- 8030-00-753-5005

Product ID:GC-408 CLASS B MSDS Date:01/01/1985 FSC:8030 NIIN:00-753-5005 **MSDS Number: BFNHQ** === Responsible Party === Company Name: GOAL CHEMICAL SEALANTS CORP. Emergency Phone Num:(213) 269-0461 CAGE:04011 === Contractor Identification === Company Name: GOAL CHEMICAL SEALANTS CORP Address:3137 E 26 TH ST Box:City:LOS ANGELES State:CA ZIP:90023-4206 Country:US Phone:213-269-0461 CAGE:04011

Ingred Name:POLYSULFIDE POLYMER(LP-POLYSULFIDE POLYMER) Fraction by Wt: 57.5%

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE) CAS:1317-65-3 RTECS #:EV9580000 Fraction by Wt: 30.3% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 11.1% OSHA PEL:15 M

G/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293
Ingred Name:STEARIC ACID CAS:57-11-4 RTECS #:WI2800000 Fraction by Wt: 0.7%
Ingred Name:THIRAM (SARA III) CAS:137-26-8 RTECS #:JO1400000 Fraction by Wt: 0.16% OSHA PEL:5 MG/M3 ACGIH TLV:1 MG/M3; 9192 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS
======================================
Effects of Overexposure: MAY CAUSE SKIN OR EYE IRRITATION UPON CONTACT
======================================
First Aid:WASH HANDS THOROUGHLY. FLUSH EYES COPIOUSLY W/WATER. GIVE EMETIC IF INGESTED.
======================================
Flash Point:400F 0C Extinguishing Media:WATER, CO*2, FOAM, DRY CHEMICAL Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE
======================================
Spill Release Procedures:MFR RECM SCRAPE UP & CLEAN W/ SOLVENTS

Н

andling and Storage Precautions:WASH HANDS THOROUGHLY AFTER HANDLING.
DO NOT INGEST. STORE INDOORS BELOW 80F.
Other Precautions:NONE

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE REQUIRED Ventilation:SUFFICIENT Protective Gloves:RECOMMENDED Eye Protection:RECOMMENDED Other Protective Equipment:NONE Supplemental Safety and Health PART A OF TWO PART PRODUCT(BASE INGREDIENTS OF SYNTHETIC RUBBER SEALING COMPOUND). TYPE II,CLASS B-2/ UNIDENT IFIED INGREDIENTS:0.24%. KEY1:N1.

HCC:N1 Boiling Pt:B.P. Text:400F,180COC Spec Gravity:1.5 Solubility in Water:MEGLIGIBLE Appearance and Odor:OFF WHITE TO GRAY SEMI-SOLID

Stability Indicator/Materials to Avoid:YES STRONG BASES & OXIDIZING AGENTS Stability Condition to Avoid:STORE BELOW 80F Hazardous Decomposition Products:SO\*2,H\*2S, OTHER SULFUR COMPOU NDS

Waste Disposal Methods: DISPOSE IAW FED., STATE & LOCAL CODES

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.