

GOAL CHEMICAL SEALANTS CORP. -- GC-408 CLASS A-2 -- 8030-00-753-5009

===== Product Identification =====

Product ID:GC-408 CLASS A-2

MSDS Date:01/01/1985

FSC:8030

NIIN:00-753-5009

MSDS Number: BFNJR

=== Responsible Party ===

Company Name:GOAL CHEMICAL SEALANTS CORP.

Address:3137 E 26TH ST

City:LOS ANGELES

State:CA

ZIP:90023-4206

Country:US

CAGE:04011

=== Contractor Identification ===

Company Name:GOAL CHEMICAL SEALANTS CORP

Address:3137 E 26TH ST

Box:City:LOS A

NGELES

State:CA

ZIP:90023-4206

Country:US

Phone:213-269-0461

CAGE:04011

===== Composition/Information on Ingredients =====

Ingred Name:POLYSULFIDE POLYMER

Fraction by Wt: 53.7%

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 26.8%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 13.4%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt

Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 5.68%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:STEARIC ACID
CAS:57-11-4
RTECS #:WI2800000
Fraction by Wt: 0.24%

===== Hazards Identification =====

Effects of Overexposure:EYE,SKIN:IRRITATION;IMHALE:DIZZINESS DUE TO
TOLUENE

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO
FRESH AIR;SKIN,EYES:FLUSH WITH LARGE AMOUNTS
OF WATER;INGESTION:ADMINISTER EMETIC. CALL DR. NOTE:WASH SKIN AFTER
EACH USE WITH SOAP AND WATER.

===== Fire Fighting Measures =====

Flash Point:77F,25C OC
Extinguishing Media:CO2, H2O, ETC.
Fire Fighting Procedures:NO SPECIAL PROCEDURES
Unusual Fire/Explosion Hazard:NO UNUSUAL HAZARDS

===== Accidental Release Measures =====

Spill Release Procedures:GENERAL CLEAN-UP, SCRAPE UP
EXCESS MATERIAL,
CLEAN RESIDUE W/SOLVENT

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 80F

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RECOMMENDED-SOLVENT VAPORS. USE NIOSH/MSHA
APPRVD RESP DEVICE
Ventilation:MFR RECM LOCAL EXHAUST
Protective Gloves:RECOMMENDED
Eye Protection:RECOMMENDED
Other Protective Equipment:NO SPECIAL EQUIP. BESIDES ABOVE
Supplemental Safety and He

alth

KEY1:F4. PART A OF TWO PART PRODUCT(BASE INGREDIENTS: SYNTHETIC RUBBER): TYPE II, CLASS A-2: UNIDENT INGRED:0.18%:DRYING TIME VARIES FROM 0.5-2HRS,BASED UPON AMT OF CATALYST ADDED:SEE DATA UNDER PN IN D B. KEY

===== Physical/Chemical Properties =====

HCC:F4

Spec Gravity:1.47

Appearance and Odor:LIGHT TO DARK GRAY WHEN MIXED;MERCAPTAN

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stab

ility Condition to Avoid:TEMPERATURES ABOVE 300F

Hazardous Decomposition Products:SO₂,H₂S, AND OTHER SULFUR COMPOUNDS

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM GENERAL TRASH DISPOSAL DISPOSE IAW FED., STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, ex

pressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.