

TELEDYNE OSTER -- BESTOIL -- 9150-00-785-3769

===== Product Identification =====

Product ID: BESTOIL

MSDS Date: 01/01/1987

FSC: 9150

NIIN: 00-785-3769

MSDS Number: BFPTQ

=== Responsible Party ===

Company Name: TELEDYNE OSTER

Emergency Phone Num: 216-943-3500

CAGE: 45168

=== Contractor Identification ===

Company Name: TELEDYNE OSTER

CAGE: 45168

===== Composition/Information on Ingredients =====

Ingred Name: SULFURIZED MINERAL OIL (CAS NO. 69029-75-0)

F

Fraction by Wt: 90.5%

Ingred Name: SULFURIZED POLY BUTENE (CAS NO. 6829-54-7)

Fraction by Wt: 6.5%

Ingred Name: SULFURIZED FAT (CAS NO. 61790-49-6)

===== Hazards Identification =====

Effects of Overexposure: EYES: SEV IRRIT, RED, TEAR. SKIN: PRLNG/RPTD

CNTCT: MOD IRRIT, DEFAT, DERMAT. INH/INGEST: NAUSEA, VOMIT, DIARR

===== First Aid Measures =====

First Aid: SKIN: THOROUGHLY WASH W/WATERLESS HAND CLEANER, THEN SOAP & WATER - DIS

CARD SOAKED CLOTHING. EYES: FLUSH W/LG AMTS OF WATER FOR 15 MIN, GET MEDICAL ATTN. INGEST: DO NOT INDUCE VOMITING - SEEK MEDICAL HELP. INH: REMOVE TO FRESH AIR, USE OXYGEN IF NEC.

===== Fire Fighting Measures =====

Flash Point: 300F COC

Extinguishing Media: FOAM, CO₂, DRY CHEMICAL

Fire Fighting Procedures: WEAR SCBA W/FULL FACE PIECE IN POSITIVE PRESSURE DEMAND

Unusual Fire/Explosion Hazard: VAP HEAVIER THAN AIR; MAY TRAVEL ALONG GROUND & BE IGNIT

AT LOCATIONS DISTANT FROM MATERIAL USE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. CONFINE SPILL. PUMP LIQUID TO STORAGE. ABSORB LIQUID W/SAND,CLAY,EARTH FLOOR ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:TREAT AS WITH NORMAL PETROLEUM CUTTING OIL.

Other Precautions:BESTOIL DOES NOT CONTAIN: AMINES

NITRITES,NITROAMINES, TRIETH

ANE AMINE,SPECIFICALLY

DIETHANOLNITROSAMINE, POLYCHLORINATED BIPHENYLS,CARCINOGENIC MATERIALS OR POLYNUCLEAR AROMATIC COMPOUNDS

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD AIR-SUPP RESP IF EXPOSURE CONDITIONS REQUIRE

Ventilation:LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:NEOP/NITRILE

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:WEAR IMPERVIOUS CLOTHING & BOOTS

Supplemental Saf

ety and Health

(DATE OF ISSUE: 11-20-85)

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.91

Solubility in Water:NO

Appearance and Odor:DARK,CLEAR LIQUID; MINERAL OIL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS (PEROXIDES,CITRIC ACID,CHLORINE,O*2)

Hazardous Decomposition Products:USUAL FOR PETROLEUM PRODUCTS

===== Disposal Considerations

=====

Waste Disposal Methods: BURN UNDER CONTROLLED CONDITIONS OR DEPOSIT IN DISPOSAL SITE. THESE METHODS MUST BE IAW FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person

utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.