View NSN Online: https://aerobasegroup.es/nsn/5970-00-810-1513

HEXCEL CORPORATION; CHEMICAL PRODUCTS DIVISION -- EPOLITE 4015 -- 5970-00-810-1513

Product ID: EPOLITE 4015 MSDS Date:06/29/1989 FSC:5970 NIIN:00-810-1513 Kit Part:Y **MSDS Number: BFQHK** === Responsible Party === Company Name: HEXCEL CORPORATION; CHEMICAL PRODUCTS DIVISION Address:20701-NORDHOFF STREET Box:2197 City:CHATSWORTH State:CA ZIP:91311-5924 Country:US Info Ph one Num:800-433-5072 0R 800-367-7527 IN CAL Emergency Phone Num:818-882-3022 Preparer's Name: P.W. CUTHBURT CAGE:01490 === Contractor Identification === Company Name: HEXCEL CORPORATION; CHEMICAL PRODUCTS DIVISION Address:20701-NORDHOFF STREET Box:2197 City:CHATSWORTH State:CA ZIP:91311-5924 Country:US Phone:818-882-3022 CAGE:01490

Ingred Name:MIXED FATTY ACID AMIDO AMINE CAS:6844-38-3 Fraction by Wt: 55-70% Other REC Limits:NON E SPECIFIED

Ingred Name:NONYLPHENOL (ALKYL PHENOL) CAS:25154-52-3 RTECS #:SM5600000 Fraction by Wt: 25-38% Other REC Limits:NONE SPECIFIED

Ingred Name:TRIETHYLENE TETRAMINE CAS:112-24-3 RTECS #:YE6650000 Fraction by Wt: 6-14% Other REC Limits:1 PPM SKIN

Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Fraction by Wt: TRACE Other REC Limits:NONE SPECIFIED OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9192

Routes of Entry:

Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN AND RESPIRATORY TRACT;SENSITIZATION OR DERMATITIS IN SENSITIVE PERSONS. CHRONIC:DERMATITIS IN SENSITIVE PERSONS.

Effects of Overexposure: MAY CAUSE IRRITATION, SENSITIZATION ORDERMATITIS IN SENSITIVE PERSONS.

Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE WORSEN.

First Aid:INHAL:RMV TO FRES H AIR. SKIN:WASH W/SOAP & WATER. EYES:FLUSH WITH WATER FOR 15 MIN. GET MED ATTN.

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODU

CTION OF HAZARDOUS DECOMPOSITION PRODUCTS SUCH AS CARBON MONOXIDE & DIOXIDE AND FUMES.
======================================
Spill Release Procedures: ABSORB EXCESS MATL IN COMBUST ABSORB. WASH AWAY RESIDUE W/DETERGENT & WATER.
======================================
Handling and Storage Precautions:STORE IN A COOL DRY AREA AWAY FM OPEN FLAME, KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FM DAMAGE. Other Precautions:AVOID CONTACT W/EYES, SKIN OR CLOTHING.
======================================
Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF CONCENTRATION IS HIGH OR POOR VENTILATION. Ventilation:MECHANICAL PREFERRED Protective Gloves:COT LINED RUBBR Eye Protection:GOGGLES/FACE SHIELD Other Protective Equipment:RUBBER APRON Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN:DO NOT USE CONTAMINATED CLOTHES;WASH AFTER EACH USE;DO NOT E AT,DRINK OR SMOKE
IN WORK A Supplemental Safety and Health MSDS REVISED DATE IS JUNE 13,1986;THIS DESCRIBES PART B OF TWO PART KIT;SEE PART INDICATOR A (HARDENER).KEY1:C2.

HCC:N1 Vapor Pres: