

MULTIGRAPHICS -- DEGLAZING SOLVENT,83-0-105532,83-9-105533 -- 6850-00-821-8882

=====
Product Identification
=====

Product ID:DEGLAZING SOLVENT,83-0-105532,83-9-105533

MSDS Date:04/01/1989

FSC:6850

NIIN:00-821-8882

MSDS Number: BFQVG

=== Responsible Party ===

Company Name:MULTIGRAPHICS

Address:1800 W CENTRAL ROAD

City:MT.PROSPECT

State:IL

ZIP:60056-2293

Country:US

Info Phone Num:312-870-5121,708-87

0-5087

Emergency Phone Num:312-870-5121 (DAY) 398-1900 (NIGHT)

CAGE:09177

=== Contractor Identification ===

Company Name:AM MULTIGRAPHICS

Address:4301 W. BROAD STREET

Box:City:RICHMOND

State:VA

ZIP:23230-3394

Country:US

Phone:804-353-0111

CAGE:1A714

Company Name:AM MULTIGRAPHICS DIV OF AM INTL INC

Address:431 LAKEVIEW CT

Box:City:MOUNT PROSPECT

State:IL

ZIP:60056-6048

Country:US

Phone:847-375-1700

CAGE:09177

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

Sta

te:KY
ZIP:42701-9804
Country:US
Phone:502-737-6757
CAGE:66172

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)
CAS:71-55-6
RTECS #:KJ2975000
Fraction by Wt: 96%
Other REC Limits:NONE SPECIFIED
OSHA PEL:350 PPM/450 STEL
ACGIH TLV:350 PPM/450STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:OTHER COMPONENTS

=====
Hazards Identification
=====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 10300 MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: MILDLY
IRRITATING. WILL DEFAT SKIN. INHALATION: SLIGHTLY TOXIC, ANESTHETIC
EFFECTS MAY OCCUR IN RANGES OF 1000 PPM. INGESTION: NOT
SIGNIFICANTLY TOXIC.
Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION, DEFATING.
INHALATION: ANESTHETIC EFFECTS. INGESTION:
N: NOT SIGNIFICANTLY TOXIC.
Medical Cond Aggravated by Exposure:INCREASED SENSITIVITY TO ADRENALIN
MAY BE CAUSED BY OVEREXPOSURE.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. SKIN: WASH AREA WITH
SOAP AND WATER. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING,
GIVE ARTIFICIAL RESPIRATION. IF BREATHING DIFFICULT GIVE OXYGEN.
GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCEVOMITING. GIVE MILK
OR USP MI

GENERAL OIL TAKE TO HOSPITAL EMERGENCY ROOM FOR FURTHER MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:NONE

Lower Limits:7.0

Upper Limits:15.0

Extinguishing Media:WATER, DRY CHEMICAL OR CARBON DIOXIDE.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS FOR POSSIBLE EXPOSURE TO HYDROGEN CHLORIDE AND TRACES OF PHOSGENE.

Unusual Fire/Explosion Hazard:VAPORS CONCENTRATED IN A CONFINED OR

POORLY VENTILATED AREAS CAN BE IGNITED ON CONTACT WITH A HIGH ENERGY SPARK, FLAME OR HIGH INTENSITY SOURCE OF HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION. CONTAIN FREE LIQUID. ABSORB ON SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage

Precautions:STORE IN COOL, DRY, WELL VENTILATED

AREA. DO NOT USE WITH ALUMINUM. KEEP AWAY FROM HEAT, OPEN FLAME AND SPARKS. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:PROTECT CONTAINERS FROM PHYSICAL DAMAGE. DO NOT REUSE CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF VAPOR CONCENTRATIONS ARE ABOVE TLV/PEL.

Ventilation:LOCAL EXHAUST TO MAINTAIN PEL/TLV (BELOW 50% OF TLV).

Protective Gloves:NEOPRENE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:PROTECTIVE CLOTHING AND APRON TO PREVENT ABSORPTION ON TO CLOTHING. PROVIDE EYE-WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

THIS IS A NEW FORMULATION. OLD FORMULATION IS SHOWN ON PNI-A. NOTE THE DIFFERENT INGREDIENTS BETWEEN

EN PNI-A AND PNI-B.

===== Physical/Chemical Properties =====

HCC:T4

Boiling Pt:B.P. Text:154F/68C

Vapor Pres:120 MMHG

Vapor Density:4.54

Spec Gravity:1.31

Evaporation Rate & Reference:0.35,(BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, COLORLESS LIQUID WITH ETHEREAL ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

CAUSTICS, OXIDIZERS AND ALUMINUM.

Stability Condi

on to Avoid:OPEN FLAMES, HOT GLOWING SURFACES OR
ELECTRIC ARC.

Hazardous Decomposition Products:HYDROGEN CHLORIDE AND POSSIBLE TRACES
OF PHOSGENE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE MATERIAL IN ACCORDANCE WITH
LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use b

y elements of the Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.