View NSN Online: https://aerobasegroup.es/nsn/8040-00-839-4919

## 3M GENERAL OFFICES -- SCOTCHGRIP 1099 PLASTIC ADHESIVE -- 8040-00-839-4919

======== Product Identification ============

Product ID:SCOTCHGRIP 1099 PLASTIC ADHESIVE

MSDS Date:06/30/1987

FSC:8040

NIIN:00-839-4919

MSDS Number: BFRZN === Responsible Party ===

Company Name: 3M GENERAL OFFICES

Address:3M CENTER City:SAINT PAUL

State:MN

ZIP:55144-1000 Country:US

Info Phone Num:612-733-1110 Emergency Phone Num:612-7

33-1110

CAGE:04963

=== Contractor Identification ===

Company Name: 3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR Box:City:SAINT PAUL

State:MN

ZIP:55144-1000 Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

====== Composition/Information on Ingredients ========

Ingred Name: ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000 Fraction by Wt: 60-70% OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

**Ingred Name** 

:SALICYLIC ACID CAS:69-72-7

RTECS #:VO0525000 Fraction by Wt: 1-10%

Other REC Limits: 2 MG/CUM

Ingred Name: ACRYLONITRILE-BUTADIENE ELASTOMER

Fraction by Wt: 10-20%

Ingred Name: PHENOL-FORMALDEHYDE RESIN

Fraction by Wt: 10-20%

Ingred Name:ZINC OXIDE

CAS:1314-13-2

RTECS #:ZH4810000 Fraction by Wt: 1-10%

OSHA PEL:15MG/M3 TDUST/5 FUME ACGIH TLV:10MG/M3 TDUST; 9293

========= Hazards Identification ==============

LD50 LC50 Mixture:NOT GIVEN Routes of Entry: Inhalation:YES Skin

:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: IRRITANT, SKIN DEFATTING, CNS

IMPAIRMENT, ORGAN DAMAGE, VISUAL IMPAIRMENT.

Effects of Overexposure:EYE:IRRITATION,

SMARTING, TEARING, REDNESS, SWELLING. SKIN: IRRITATION, DRYNESS,

CRACKING. INHALATION: RESP SYSTEM IRRITATION, CNS

EFFECTS-DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHES, NUMBNESS, VISUAL

EFFECT S,UNCONSC. INGESTION: IRRITATION, ASPIRATION PNEUMONIA

POSSIBLE, NAUSE

A, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure: ANY PREEXISTING ALLERGY, SENSITIVITY OR ORGAN DYSFUNCTION.

First Aid:EYE:FLUSH 15 MIN W/AMPLE WATER. SKIN:WASH W/SOAP & WATER. INHALATION:REMOVE TO FRESH AIR.GIVE ART RESP OR OXYGEN AS REQUIRED. INGESTION:DO NOT INDUCE VOMITING.IF CONSCIOUS, GIVE TWO GLASSES MILK OR WA TER.IF VOMITING,LOWER VICTIM'S HEAD BELOW HIP LEVEL TO PREVENT ASPIRATION; CALL P

HYSICIAN ALL EXPOSURES THAT ARE SEVERE OR PROLONGED. Flash Point:OF;-17.8C, CC Lower Limits:2.6 Upper Limits:12.8 Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL. Fire Fighting Procedures: USE SCBA PP MODE FIGHTING FIRES. Unusual Fire/Explosion Hazard: EXTREMELY FLAMMABLE! OVERHEATED CONTAINERS MAY RUPTURE OR EXPLODE. ======== Accidental Release Measures ============ Spill Release Procedures:O BSERVE ALL PRECAUTIONS GIVEN. REMOVE IGNITION & HEAT SOURCES, STOP LEAK. CONFINE SPILL. COLLECT SPILLAGE USING ABSORBENT MATERIAL, PLACE IN CLOSABLE CONTAINERS. =========== Handling and Storage ============================ Handling and Storage Precautions: AVOID HEAT & IGNITION SOURCES. STORE IN COOL, DRY AREA SUITABLE FOR FLAMMABLE MATERIAL. KEEP CONTAINERS CLOSED. Other Precautions: VAPORS GIEN OFF BY PRODUCT CAN EASILY BE IGNITED. AVOID EYE CONTACT, PROLONGED BREATHING OF VAPORS 6 PROLONGED OR REPEATED SKIN CONTACT. KEEP CONTAINER CLOSED, BP IS FOR ACETONE ====== Exposure Controls/Personal Protection ======== Respiratory Protection: NONE IF LOCAL EXHAUST MAINTAINED. Ventilation: USE LOCAL VENTILATION; SPRAY BOOTH OR PARTICULATE (MIST) RESPIRATOR AS REQUIRED. Protective Gloves:IMPERVIOUS. Eye Protection: CHEMICAL GOGGLES; FULL FACE SHIELD. Other Protective Equipment: EYE SAFETY GLASSES OR AS ALTERNATE. Work Hygienic Practices: AVOID EYE-SKIN CONTACT. DO NOT INHALE OR INGEST. Supplemental Safety and Health UPDATE PER 3M MSDS DOC#10-2442-1 30JUN87. 3M GENERIC ID# IS 62-1099-XXXX-X. PART NAME FORMERLY SCOTCHGRIP EC-1099. ========= Physical/Chemical Properties =========== HCC:F2 Boiling Pt:B.P. Text:131F;55C Vapor Pres:180 Vapor Density:2.0 Spec Gravity:0.89 Viscosity:2150 CPS Evaporation Rate & Department Reference: 1.9(ETHER= 1) Solubility in Water:SLIGHT Appearance and Odor:LIGHT TAN LIQUID, KETONE ODOR Percent V

olatiles by volume.or
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES OXIDIZERS. Stability Condition to Avoid:EXCESS HEAT & IGNITION SOURCES. Hazardous Decomposition Products:CARBON OXIDES, NITROGEN COMPOUNDS INCLUDING POSSIBLE HYDROGEN CYANIDE.
====== Disposal Considerations ===========
Waste Disposal Methods:RECLAIM OR INCINERATE IAW ALL LAWS & REGS.

Disclaimer (provided with this information by the compiling agencies):

alatilaa by Valuma 67

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.