

DOW CORNING CORP. -- A-4094 PRIMER -- 8040-00-845-4304

===== Product Identification =====

Product ID:A-4094 PRIMER

MSDS Date:01/01/1985

FSC:8040

NIIN:00-845-4304

MSDS Number: BFSJX

=== Responsible Party ===

Company Name:DOW CORNING CORP.

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Emergency Phone Num:517-496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address

:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: >80%

OSHA PEL:100 PPM

===== Hazards Identification =====

=====

Effects of Overexposure:MAY CAUSE SLIGHT ANESTHESIA, HEADACHES, ETC.;  
SKIN/EYES: IRRITATES;

===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION.  
SKIN/EYES- FLUSH WITH WATER.

===== Fire Fighting Measures =====

Flash Point:50 F OC  
Lower Limits:1.2  
Upper Limits:6.0  
Extinguishing Media:CO\*2, FOAM  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:NONE

=

===== Accidental Release Measures =====

Spill Release Procedures:MOP, WIPE,OR SOAK UP W/ABSORBENT MATERIAL  
USING PROPER PROTECTIVE EQUIPMENT.

===== Handling and Storage =====

Handling and Storage Precautions:SAME PRECAUTIONS AS FOR ANY FLAM.  
PRODUCT

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC VAPOR TYPE  
Ventilation:MECHANICAL TYPE REQUIRED  
Protective Gloves:RUBBER/PLA  
STIC  
Eye Protection:SAFETY GLASSES  
Other Protective Equipment:AS REQUIRED BY YOUR ORGANIZATION & LOCAL  
POLICY.  
Supplemental Safety and Health  
KEY1:F3.

===== Physical/Chemical Properties =====

HCC:F2  
Boiling Pt:B.P. Text:210 F  
Vapor Pres:25  
Vapor Density:>1.  
Spec Gravity:0.9  
Evaporation Rate & Reference:(ETHER =1 ) < 1.  
Solubility in Water:10.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NONE

KNOWN

Stability Condition to Avoid:SOURCES OF IGNITION, SPARKS, ETC.

Hazardous Decomposition Products:METAL OXIDES,CO\*2, TRACES OF  
INCOMPLETE BURNED CARBON PRDS.

===== Disposal Considerations =====

Waste Disposal Methods:REFER TO FEDERAL, STATE, & LOCAL REGULATIONS &  
STATUTES RELATIVE TO SOLVENT DISPOSAL. RESIDUE FROM EVAPORATED  
SOLVENT CAN BE LAND FILLED OR BURNED IAW LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling  
agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.