

H B FULLER CO -- SC-0840 -- 8040-00-869-8792

===== Product Identification =====

Product ID:SC-0840

MSDS Date:01/01/1987

FSC:8040

NIIN:00-869-8792

MSDS Number: BFTHM

=== Responsible Party ===

Company Name:H B FULLER CO

Address:2400 KASOTA AVE

City:ST PAUL

State:MN

ZIP:55108-1511

Country:US

CAGE:R1331

=== Contractor Identification ===

Company Name:FULLER H B CO

Address:2400 KASOTA AVE

Box:City:ST PA

UL

State:MN

ZIP:55108-1511

Country:US

Phone:612-645-3401

CAGE:92528

Company Name:H B FULLER CO

Address:1200 WOLTERS BLVD

City:VADNAIS HEIGHTS

State:MN

ZIP:55110

Country:US

Phone:612-481-3300

CAGE:R1331

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: >10%

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RT

ECS #:GW1050000
Fraction by Wt: 1-10%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: >10%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: >10%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rp
t Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:EYE:IRRIT.SKIN:LIQ CONTACT WILL DRY,DEFAT
SKIN.RPTD,PRLG CONTACT MAY CAUSE IRRIT,DERMAT.SEE SUPP

===== First Aid Measures =====

First Aid:EYE:FLUSH IMMED W/ LARGE AMOUNTS OF H*2O FOR A LEAST 15
MIN.CALL A PHYSICIAN.SKIN:WASH AFFECTED AREA W/ SOAP,WATER.LAUNDER
CONTAM CLOTH BEFORE REUSE.INHAL:REMOVE FROM EXPOS.RESTORE BREATH IF
NECES
SARY .KEEP WARM & QUIET.CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:0F,-18C TCC
Lower Limits:1.2
Extinguishing Media:WATER SPRAY,FOAM,DRY CHEMICAL OR CO*2
Fire Fighting Procedures:USE SCBA & FULL PROTECTIVE EQUIPMENT
Unusual Fire/Explosion Hazard:POSSIB PRESSURE BUILD UP IN CLOSED CONTNR
WHEN HEATED.WATER SPRAY MAY BE USED TO COOL CONTNR

===== Accidental Release Measures =====

Spill Release Procedures:REMO

VE ALL SOURCES OF IGNITION. VENTILATE
AREA. AVOID BREATH VAP. DIKE & CONTAIN SPILL W/ INERT ABSORBENT &
TRANSFER TO CONTNR FOR DISPOSAL. USE NON-SPARKING TOOLS. KEEP SPILL
OUT OF SEWERS

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COMPLIANCE W/ OSHA 1910.106. DO
NOT STORE NEAR HEAT, SPARKS OR FLAME. KEEP CONTNR CLOSED. DO NOT CUT
OR WELD NEAR THIS CONTNR

Other Precautions: DRUMS OF THIS MATERIAL SHOULD BE GROUNDED WHEN

POURING. AVOID BREATH VAP. USE ONLY W/ ADEQUATE VENT. AVOID CONTACT W/
EYE, SKIN, CLOTH. WASH THOROUGHLY AFTER HANDLING. OBS ALL LABEL
SAFEGUARD

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NIOSH/MSHA APPROVD RESPIR. ORGANIC VAPOR RESP
WHEN EXPOSURE LIMITS ARE EXCEEDED

Ventilation: LOCAL EXHAUST

Protective Gloves: RUBBER

Eye Protection: SAFETY GLASS, CHEM GOGGLE

Other Protective Equipment: EYE WASHES. IMPERVIOUS CLOTH & BOOT

Supplemental Safety and Health

M

SDS PREP: 21 NOV 86. SPEC: TYPE III. OVEREXPOSURE: INHALATION IN POORLY VENT AREAS
WILL CAUSE IRRITATION OF THE NOSE, THROAT, RESPIRATORY TRACT & MAY CAUSE
DIZZINESS, HEADACHE, NAUSEA OR UNCONSCIOUSNESS

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: >133F, >56C

Spec Gravity: 0.86

Viscosity: 950 CPS

Solubility in Water: NON-MISCIBLE

Appearance and Odor: LIQUID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products

ducts:INCOMPLETE COMBUST CAN YIELD LOW MW
HYDROCARBONS,CO

===== Disposal Considerations =====

Waste Disposal Methods:THIS PRODUCT MEETS THE DEFINITION OF HAZ WASTE
UNDER THE USEPA HAZ WASTE REG 40CFR261.IT IS IGNITABLE WASTE CLASS
D001.DISPOSAL VIA INCINERATION IS RECOMMENDED.DISPOSAL IN
ACCORDANCE W/ LOCAL,STATE,FEDERAL REGULATION

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by
elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.