

PRODUCTS RESEARCH & CHEMICAL CORP. -- PR-1201-Q -- 8030-00-881-2618

===== Product Identification =====

Product ID:PR-1201-Q

MSDS Date:01/01/1985

FSC:8030

NIIN:00-881-2618

MSDS Number: BFTRJ

=== Responsible Party ===

Company Name:PRODUCTS RESEARCH & CHEMICAL CORP.

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:818-

240-2060

CAGE:DO563

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

Company Name:PRODUCTS RESEARCH & CHEMICAL

Address:NOW DBA COURTAULDS AEROSPACE

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Phone:818-240-2060

CAGE:DO563

===== Composition/Information on Ingredients =====

Ingred Name:LEAD PEROXIDE (LEAD DIOXIDE), (

OSHA PEL FROM 29CFR
1910.1025)
CAS:1309-60-0
RTECS #:OG0700000
Fraction by Wt: 7%
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.15 MG/M3(PB); 8990

===== Hazards Identification =====

Effects of Overexposure:ACCELERATOR CONTAINS LEAD COMPOUND WHICH MAY BE
ABSORBED THROUGH BREAKS IN SKIN.

===== First Aid Measures =====

First Aid:SKIN:WASH THOROUGHLY WITH SOAP AND WATER.EYES:FLUSH
THOROUGHLY WITH LARGE AMOUNTS OF WATER.IN
GESTION:INDUCE
VOMITING.INHALATION:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF
NECESSARY.GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:>200F PMCC
Lower Limits:UNK
Upper Limits:UNK
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE.
Fire Fighting Procedures:WEAR AIR-SUPPLIED RESPIRATOR WHILE FIGHTING
FIRES.
Unusual Fire/Explosion Hazard:EMISSION OF TOXIC VAPORS

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK AT SOURCE.ELIMINATE IGNITION
SOURCES.ABSORB EXCESS WITH RAGS,PAPER TOWELS OR OTHER ABSORBENT
MATERIAL.CLEAN AREA WITH XYLENE OR TOLUENE.PLACE IN CLOSED
CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IN CLOSED CONTAINERS AT ROOM
TEMPERATURE.AVOID FIRE HAZARDS.PROTECT FROM PHYSICAL DAMAGE.AVOID
ACCELERATOR SPILLAGE.

===== Exposure Controls/Personal Protection

=====

Respiratory Protection: AIR SUPPLIED RESPIRATOR RECOMMENDED IN CONFINED AREAS.

Ventilation: MECHANICAL/LOCAL EXHAUST TO MINIMIZE SOLVENT VAPOR BELOW TLV

Protective Gloves: POLYETHYLENE

Eye Protection: CHEM GOGGLES

Other Protective Equipment: USE PROTECTIVE HAND CREAM

Supplemental Safety and Health

ITEM IS UNDER CLASS 1 IN MIL SPEC 8516. KEY1: D2.

===== Physical/Chemical Properties =====

HCC: D1

Spec Gravity: UNK

Solubility in Water: NEGLIGIBLE

Appearance

and Odor: PINKISH-BROWN SYRUP; SLIGHT TOLUENE ODOR

Percent Volatiles by Volume: UNK

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

DECOMPOSES WHEN EXPOSED TO STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: AVOID IGNITION SOURCES

Hazardous Decomposition Products: OXIDES OF SULFUR; HYDROGEN SULFIDE; FORMIC ACID.

===== Disposal Considerations =====

Waste Disposal Methods: PLACE ABSORBED MATERIAL IN CLOSED CONTAINERS AND

DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional

I advice to verify and
assume responsibility for the suitability of this information to their
particular situation.