

PRODUCTS RESEARCH & CHEMICAL CORP. -- PR-1201-Q -- 8030-00-881-2618

===== Product Identification =====

Product ID:PR-1201-Q

MSDS Date:01/01/1985

FSC:8030

NIIN:00-881-2618

MSDS Number: BFTRK

=== Responsible Party ===

Company Name:PRODUCTS RESEARCH & CHEMICAL CORP.

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:818-

240-2060

CAGE:DO563

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

Company Name:PRODUCTS RESEARCH & CHEMICAL

Address:NOW DBA COURTAULDS AEROSPACE

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Phone:818-240-2060

CAGE:DO563

===== Composition/Information on Ingredients =====

Ingred Name:POLYSULFIDE POLYMER

Fraction by

Wt: 50%

Ingred Name:PIGMENTS
Fraction by Wt: 35%

Ingred Name:RESINS & PLASTICIZERS
Fraction by Wt: 3%

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 4%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM; Z-2
ACGIH TLV:S, 50 PPM; 9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:BASE COMPOUND MAY BE IRRITATING TI SKIN,EYES.

===== First Aid Measures =
=====

First Aid:SKIN:WASH THOROUGHLY WITH SOAP AND WATER.EYES:FLUSH THOROUGHLY WITH LARGE AMOUNTS OF WATER.INGESTION:INDUCE VOMITING.INHALATION:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NECESSARY.GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:>73F PMCC
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE
Fire Fighting Procedures:WEAR AIR-SUPPLIED RESPIRATOR WHILE FIGHTING
F
IRES.
Unusual Fire/Explosion Hazard:EMISSION OF TOXIC VAPORS

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK AT SOURCE.ELIMINATE IGNITION SOURCES.ABSORB EXCESS WITH RAGS,PAPER TOWELS OR OTHER ABSORBENT MATERIAL.CLEAN AREA WITH XYLENE OR TOLUENE.PLACE IN CLOSED CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IN CLOSED CONTAINERS AT ROOM TEMPERATURE.AVOID

FIRE HAZARDS.PROTECT FROM PHYSICAL DAMAGE.AVOID
ACCELERATOR SPILLAGE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR SUPPLIED RESPIRATOR RECOMMENDED IN CONFINED
AREAS.
Ventilation:MECHANICAL/LOCAL EXHAUST TO MINIMIZE SOLVENT VAPOR BELOW
TLV
Protective Gloves:POLYETHYLENE
Eye Protection:CHEM GOGGLES
Other Protective Equipment:USE PROTECTIVE HAND CREAM.
Supplemental Safety and Health
ITEM IS A CLASS 1 UNDER MIL SPEC 8516.KEY1:J1.

=====
===== Physical/Chemical Properties =====

HCC:D1
Spec Gravity:1.7
Solubility in Water:NEGLIGIBLE
Appearance and Odor:PINKISH BROWN SYRUP;SLIGHT TOLUENE ODOR.
Percent Volatiles by Volume:6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
DECOMPOSES WHEN EXPOSED TO STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:AVOID IGNITION SOURCES
Hazardous Decomposition Products:OXIDES OF SULFUR;HYDROGEN
SULFIDE;
FORMIC AICD.

===== Disposal Considerations =====

Waste Disposal Methods:PLACE ABSORBED MATL IN CLOSED CONTAINERS AND
DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.DO
NOT INCINERATE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information

to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.