

GC THORSEN -- RED GLPT VARNISH, 10-9002. -- 5970-00-901-5331

===== Product Identification =====

Product ID:RED GLPT VARNISH, 10-9002.

MSDS Date:11/18/1997

FSC:5970

NIIN:00-901-5331

MSDS Number: BFVNQ

==== Responsible Party ===

Company Name:GC THORSEN

Address:1801 MORGAN ST

Box:1209

City:ROCKFORD

State:IL

ZIP:61105-1209

Country:US

Info Phone Num:815-968-9661

Emergency Phone Num:815-968-9661

Preparer

's Name:M. WINSEL

CAGE:EO177

==== Contractor Identification ===

Company Name:GC THORSEN

Address:1801 MORGAN STREET

Box:City:ROCKFORD

State:IL

ZIP:61105

Country:US

Phone:815-968-9661

CAGE:72653

Company Name:GC THORSEN

Address:1801 MORGAN STREET

Box:1209

City:ROCKFORD

State:IL

ZIP:61105-1209

Country:US

Phone:815-968-9661

CAGE:EO177

Company Name:PEAK ELECTRONICS CORP

Address:354-356 W LANCASTER AVE

Box:533

City:WAYNE

State:PA

ZIP:19087-3925

Country:US

CAGE:66274

===== Composition/Informati

on on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 62%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:PIGMENT (IRON OXIDE)

CAS:1309-37-1

RTECS #:NO7400000

Fraction by Wt: 36%

Other REC Limits:NONE SPECIFIED

OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:AKLYD RESIN

CAS:68459-31-4

Fraction by Wt: 2%

Or

her REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INFLAMMATION OF SKIN & RESPIRATORY
TRACT, BREATHING DIFFICULTY.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.

Effects of Overexposure:HEADACHE

HE, DIZZINESS, NAUSEA, UNCOORDINATION,

NARCOSIS, ANEMIA, PARTIAL PARALYSIS OF EXTREMITIES.

Medical Cond Aggravated by Exposure:AVOID EXPOSURE OF PERSONS WITH
DISEASES OF BLOOD, LIVER, KIDNEY OR CENTRAL NERVOUS SYSTEM.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/ OXYGEN IF
NEEDED. EYE CONTACT:FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL
HELP. SKIN CONTACT:WASH WITH SOAP AND WATER. GET MED ATTENTION IF

SYMPTOMS PERSI ST. INGESTION:DO NOT INDUCE VOMITING, GET MEDICAL HELP IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:85.0F,29.4C

Lower Limits:1%

Upper Limits:6%

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL FIRE PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.

Unusual Fire/Explosion Hazard:VAPORS MAY TRAVEL L

ONG DISTANCES AND

FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES, VENTILATE AREA, CLEAN UP WITH ABSORBENT MATERIAL. AVOID BREATHING FUMES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS SEALED AND AWAY FROM HEAT OR IGNITION SOURCES.

Other Precautions:AVOID PROLONGED BREATHING OF VAPORS OR CONTACT WITH SKIN.

=====

Exposure Controls/Personal Protection =====

Respiratory Protection:CHEMICAL CARTRIDGE RESPIRATOR OR SELF-CONTAINED BREATHING APPARATUS.

Ventilation:MECHANICAL(GENERAL) EXHAUST AS REQUIRED TO MEET TLV LIMITS.

Protective Gloves:NEOPRENE OR NITRILE RUBBER GLOVES

Eye Protection:CHEMICAL GOGGLES/FACE SHIELD

Other Protective Equipment:RESISTANT APRON AS REQUIRED.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING.

Supplemental Safety and He

alth

NONE

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:285F,141C

Vapor Pres:10

Vapor Density:3.7

Spec Gravity:1.1

Evaporation Rate & Reference:0.19 (N-BUTYL ACETATE=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:RED LIQUID, AROMATIC SOLVENT ODOR.

Percent Volatiles by Volume:62

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS.

Stability Condition to A

void:HEAT, FLAMES OR SPARKS.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE AT A LICENSED FACILITY OR DISPOSE OF
IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner w

hatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.