View NSN Online: https://aerobasegroup.es/nsn/8030-00-926-2135 DYNATRON/BONDO CORP. -- BONDO -- 8010-00-926-2135 ============ Product Identification ========================= Product ID:BONDO MSDS Date:01/01/1987 FSC:8010 NIIN:00-926-2135 Kit Part:Y MSDS Number: BFWTW === Responsible Party === Company Name: DYNATRON/BONDO CORP. Emergency Phone Num:404-351-2730 CAGE:16522 === Contractor Identification === Company Name: BONDO/MAR-HYDE CORP Address:3700 ATLANTA INDUSTRIAL PKWY NW Box:City:A **TLANTA** State:GA ZIP:30331 Country:US Phone:404-696-2730 CAGE:16522 ======= Composition/Information on Ingredients ======== Ingred Name:TITANIUM DIOXIDE Ingred Name: STYRENE MONOMER **ACGIH TLV:100 PPM** Ingred Name: ANILINE (SARA III) CAS:62-53-3 RTECS #:BW6650000 OSHA PEL:S, 5 PPM ACGIH TLV:S, 2 PPM; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

========= Hazards Identification =============

Effects of Overexposure: EYE/SKIN IRRITATION; RESPIRATORY TRACT

| IRRITATION |
|--|
| ====================================== |
| First Aid:WASH SKIN WITH SOAP AND WATER; FLUSH EYES WITH WATER 15 MINUTES; CALL DOCTOR; REMOVE TO FRESH AIR |
| ====================================== |
| Flash Point:100F,37.8C TOC Lower Limits:1.1 Upper Limits:6.1 Extinguishing Media:WATER,CARBON DIOXIDE,FOAM SODIUM BICARBONATE Fire Fighting Procedures:VENT SMOKE; USE GAS MASK OR REMATE AIR SUPPLY |
| ========== Accidental Releas e Measures ==================================== |
| Spill Release Procedures:SHOVELING AND WIPING |
| =========== Handling and Storage ============ |
| Handling and Storage Precautions:DO NOT STORE AT HIGH TEMPERATURES |
| ====== Exposure Controls/Personal Protection ======== |
| Respiratory Protection:ADEQUATE VENTILATION Ventilation:LOCAL EXHAUST Eye Protection:RECOMMENDED Supplemental Safety and Health 2 PART KIT; POLYESTER RESIN 40 PERCET; MAGNESIUM/SILICATE 59 PERCENT; PIGMENT 1 PER CENT |
| ========= Physical/Chemical Properties ========= |
| HCC:F4 Boiling Pt:B.P. Text:295F,146.1C Vapor Pres:7.0 Vapor Density:3.6 Spec Gravity:1.79 Evaporation Rate & Dublity in Water:SLIGHT Appearance and Odor:GRAY,VISCOUS COMPOUND, PUNGENT ODOR Percent Volatiles by Volume:16.0 |
| ========= Stability and Reactivity Data ========== |
| Stability Indicator/Materials to Avoid:VES |

Stability Indicator/Materials to Avoid:YES ORGANIC PEROXIDES Stability Condition to Avoid:EXPOSU

RE TO IGNITION SOURCES IN CONFINED AREAS

Hazardous Decomposition Products:STYRENE VAPORS
Conditions to Avoid Polymerization:CONTACT WITH ORGANIC PEROXIDES

======= Disposal Considerations ===========

Waste Disposal Methods: APPROVED LANDFILL

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or impli

ed, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.